


ÖLFLEX® VFD SLIM

Reduced-diameter VFD cable; 600V/1000V; UL & c(UL) TC-ER approval



ÖLFLEX® VFD SLIM is a reduced-diameter shielded motor cable for VFD drives. It is designed with the LAPP Surge Guard insulation system, which includes a semiconductive layer made to withstand nonlinear power distortions associated with VFD drives and to disperse increases in voltage caused by wave reflection, spikes, in-rush current, and harmonics. It is resistant to a wide range of disinfecting solutions used in the food, beverage, chemical and related industries.

Recommended applications

VFD drive and motor applications; web presses; HVAC; conveyors; on/off, slow down/speed up applications

Approvals



Cable attributes		page 648	
OIL	OR-03	FLAME	FR-03
MOTION	FL-01	MECH.	MP-03

Construction

Conductors: finely stranded tinned copper

Insulation: LAPP Surge Guard insulation system

Shielding: barrier tape; triple layer foil tape (100% coverage); tinned copper braid (85% coverage)

Jacket: specially formulated thermoplastic polymer; black

Application Advantage

- LAPP Surge Guard insulation protection
- UL TC-ER & c(UL) CIC/TC approved
- Double shielded for extra protection
- Resistant to a wide range of disinfecting solutions used in the food, beverage, chemical and related industries, according to ECOLAB® PM 40-1 test procedure

Complete the installation	
SKINTOP® MS-SC page 522	EPIC® ULTRA HB page 404

Technical data

Minimum bend radius:	7.5 x cable diameter	Color code:	black with white numbers, plus green/yellow ground
Temperature range:	- UL/CSA TC: -25°C to +90°C - for stationary use: -40°C to +105°C - for flexible use: -25°C to +105°C	Approvals:	UL: TC-ER per UL 1277 MTW per UL 1063 WTTCC per UL 2277 AWM 20886 Attributes: UL Oil Res I/II 75°C wet; 90°C dry -40°C cold bend; -25° cold impact sunlight resistant Submersible pump (14 AWG & larger) direct burial NFPA 79 NEC: Class 1 Division 2 per NEC Article 501 Canada: c(UL) CIC/TC FT4 CSA AWM I/II A/B 1000V FT4 Additional: MSHA P-07KA050013-MSHA CE & RoHS
Nominal voltage:	- UL/CSA TC: 600V - UL WTTCC: 1000V - UL Flexible Motor Supply: 1000V - UL/CSA AWM: 1000V		
Test voltage:	2000V		
Peak voltage:	7500V		
Conductor stranding:	- 18 - 6 AWG: Class 5 fine wire* - 4 - 2 AWG: Class K fine wire * 18 AWG meets only Class 5 cross section and DC resistance		

Part number	Number of conductors incl. ground	Nominal outer diameter in mm	Copper weight lbs/mft	Approx. weight lbs/mft	SKINTOP® MS-SC PG thread	SKINTOP® MS-M BRUSH metric thread
18 AWG (1 mm²)						
761804	4	0.394	10.0	53	112	53112230
16 AWG (1.5 mm²)						
761604	4 + drain	0.465	11.8	73	154	53112240
14 AWG (2.5 mm²)						
761404	4	0.514	13.1	100	194	53112240
12 AWG (4 mm²)						
761204	4	0.583	14.8	139	254	53112250
10 AWG (6 mm²)						
761004	4	0.697	17.7	195	346	53112260

Part number	Number of conductors incl. ground	Nominal outer diameter in mm	Copper weight lbs/mft	Approx. weight lbs/mft	SKINTOP® MS-SC PG thread	SKINTOP® MS-M BRUSH metric thread
8 AWG (10 mm²)						
760804	4	0.829	21.1	326	596	53112260
6 AWG (16 mm²)						
760604	4	1.002	25.5	494	785	53112270
4 AWG (21 mm²)						
760404	4	1.186	30.1	648	965	53112270
2 AWG (33.7 mm²)						
760204	4	1.395	35.4	985	1339	53112680

Ecolab® is a registered trademark of Ecolab, Inc.

Recommended SKINTOP® assumes minimal OD variance. Additional configurations are available; please see our SKINTOP® section.

If not otherwise specified, all values relating to the product are nominal values. Photographs are not to scale and are not true representations of the products in question.