

SKINDICHT® SM/SM-M

Nickel-plated brass locknuts for NPT, PG & metric strain relief cable glands



SKINDICHT® SM locknuts are required wherever NPT, PG or metric cable glands must be fastened to a housing, and tapped holes cannot be provided.

Technical data

Material:
 - NPT: stamped steel
 - PG & metric: nickel-plated brass

Temperature range: -20°C to +100°C

Approvals



NPT

| Part number | Size | Wrenching flats | Nut thickness in | Pack size |
|-------------|----------|-----------------|------------------|-----------|
| 811092* | NPT 3/8" | 0.945 | 0.138 | 100 |
| 811093 | NPT 1/2" | 1.102 | 0.157 | 100 |
| 811094 | NPT 3/4" | 1.378 | 0.157 | 50 |
| 811095 | NPT 1" | 1.693 | 0.157 | 50 |

*Product features a hex design

PG

| Part number | Size | Wrenching flats | Nut thickness in | Pack size |
|-------------|-------|-----------------|------------------|-----------|
| 52003490 | PG 7 | 0.591 | 0.110 | 100 |
| 52003500 | PG 9 | 0.709 | 0.110 | 100 |
| 52003510 | PG 11 | 0.827 | 0.118 | 100 |
| 52003520 | PG 13 | 0.906 | 0.118 | 100 |
| 52003530 | PG 16 | 1.024 | 0.118 | 100 |
| 52003540 | PG 21 | 1.260 | 0.138 | 50 |
| 52003550 | PG 29 | 1.614 | 0.138 | 50 |
| 52003560 | PG 36 | 2.009 | 0.197 | 25 |
| 52003570 | PG 42 | 2.364 | 0.197 | 25 |
| 52003580 | PG 48 | 2.521 | 0.216 | 25 |

metric

| Part number | Size | Wrenching flats | Nut thickness in | Pack size |
|-------------|------------|-----------------|------------------|-----------|
| 52103000 | M12 x 1.5 | 0.591 | 0.118 | 100 |
| 52103010 | M16 x 1.5 | 0.748 | 0.118 | 100 |
| 52103020 | M20 x 1.5 | 0.945 | 0.138 | 100 |
| 52103030 | M25 x 1.5 | 1.182 | 0.157 | 100 |
| 52103040 | M32 x 1.5 | 1.418 | 0.157 | 100 |
| 52103050 | M40 x 1.5 | 1.812 | 0.197 | 50 |
| 52103060 | M50 x 1.5 | 2.364 | 0.197 | 50 |
| 52103070 | M63 x 1.5 | 2.758 | 0.197 | 25 |
| 52103071 | M75 x 1.5 | 3.349 | 0.315 | 5 |
| 52103072 | M90 x 2.0 | 4.018 | 0.394 | 1 |
| 52103073 | M110 x 2.0 | 4.885 | 0.472 | 1 |



800.633.6339

www.lapptannehill.com