


## STANDARD CABLE TIES

A




See page A-32 for mil-specs

### Intermediate 30lb, 40lb Natural, UV Black

Per Bag	Part no.	Colour & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case	ANSI/UL 62275 TYPE
1,000	L-5409M	Natural Nylon	5.84/148.33	.140/3.556	.049/1.244	40lb	1.437/36.512	UL-CSA MS3367-S*	10,000	21
100	L-5409C									
1,000	L-5400M	UV Black Nylon								
100	L-5400C									
1,000	L-8409M	Natural Nylon	8.875/225.42	.140/3.556	.049/1.244	40lb	2.375/60.325	UL-CSA	10,000	21
100	L-8409C									
1,000	L-8400M	UV Black Nylon								
100	L-8400C									
100	L-11409C	Natural Nylon	11.56/293.67	.140/3.556	.058/1.473	40lb	3.375/85.72	UL-CSA	5,000	21
100	L-11400C	UV Black Nylon								
100	L-14409C	Natural Nylon	14.50/368.30	.140/3.556	.058/1.473	40lb	4.00/101.60	UL-CSA	5,000	21
100	L-14400C	UV Black Nylon								

Tolerance: .XXX = ±.005, .XX = ±.015, Fraction = ±1/32"



### Standard 50lb Natural, UV Black

Per Bag	Part no.	Colour & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case	ANSI/UL 62275 TYPE
1,000	L-7509M	Natural Nylon	7.56/192.07	.180/4.572	.052/1.320	50lb	1.875/47.625	UL-CSA MS3367-1*	10,000	21S
100	L-7509C									
1,000	L-7500M	UV Black Nylon								
100	L-7500C									21S
500	L-11509D	Natural Nylon	11.25/285.75	.180/4.572	.052/1.320	50lb	3.062/77.787	UL-CSA MS3367-7*	5,000	21S
100	L-11509C									
500	L-11500D	UV Black Nylon								
100	L-11500C								21S	
500	L-14509D	Natural Nylon	14.56/369.87	.180/4.572	.052/1.320	50lb	4.125/104.775	UL-CSA MS3367-2*	5,000	21S
100	L-14509C									
500	L-14500D	UV Black Nylon								
100	L-14500C								21S	
100	L-17509C	Natural Nylon	17.09/434.16	.187/4.749	.060/1.524	50lb	4.75/120.65	UL	5,000	21
100	L-17500C	UV Black Nylon								

**NOW 21S!**

Tolerance: .XXX = ±.005, .XX = ±.015, Fraction = ±1/32"

MADE IN U.S.A.

