THIS	COPY IS F	ROVID	ED ON	A RESTRICTED BASIS AND IS NOT TO BE US	ED IN ANY WAY DETRIMENTA	L TO TI		ERESTS OF PANDUIT CORP.	
Material				High Conductivity Seamless Copper Tube					
Plating				Electro-Tin					
W	Wire Size			1/0 AWG				63 R Ref	
W	Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric				Color coded barrel markings	
W	Wire Strip Length			1.0 in.	.80±.04	\rightarrow			
St	Stud Size			1/2 in.					
	UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.63±.04		— 1.7	5±.02	
	UL Temperature Rating			90°C	I				
	C.S.A Certified Wire Connector			Yes					
	Panduit Color Code on Barrel			PINK					
	Panduit Die Index No. on Barrel		ex No.	P42		Wire	inspe	ction window94±.04 - Beveled wire entry	
Di	Alternate Industry Die Index No. () on Barrel			(12)	l i			.39±.01 .52±.01	
CERTIFIED LISTED Wire Connector									
								ANDUIT CORP. TINLEY PARK, ILLINOIS	
								LCD1/0-12-X Copper Lug - Two-Hole, Standard Barrel	
)1	7/12		JHNU	REMOVED NAVY NUMBER	N10884TG-LCD1/0-12-CUST			SCALE DRAWING NO / CAD EILE	
EV	DATE	BY	СНК	DESCRIPTION	ECN	-R	SUP	N/A LCD1_0-12-CUST	