



Ceramic Metal Halide Lamps

EYE CERA ARC™

Tubular Shape

Features and Benefits

- Widest range of colour temperatures in the industry
- Blocks UV to prevent discoloration and fading
- 85% lumen maintenance makes it possible to reduce energy consumption up to 50%
- Excellent colour rendition for red objects
- Reduced colour shift
- High efficacy
- CRI of 90+

Applications

- Museums
- Art galleries
- Jewellery boutiques
- Commercial and retail facilities

T4.5



Dia. = 0.59 in. (15 mm)
MOL = 3.35 in. (85 mm)
LCL = 2.05 in. (52 mm)

T6 (35 W-70 W)



Dia. = 0.79 in. (20 mm)
MOL = 4.06 in. (103 mm)
LCL = 2.21 in. (56 mm)

T6 (150 W)



Dia. = 0.79 in. (20 mm)
MOL = 4.33 in. (110 mm)
LCL = 2.21 in. (56 mm)

| Order Code | Description | Watts (W) | Base | Colour Temp. (K) | ANSI code | CRI | Average life (hrs) | Initial lumens (lm) | Mean lumens (lm) | Burn pos. | Finish | Luminaire | Case qty |
|-------------|----------------------|-----------|------|------------------|-----------|-----|--------------------|---------------------|------------------|-----------|--------|-----------|----------|
| T4.5 | | | | | | | | | | | | | |
| 58133 | CMT35/U/930/G8.5 EYE | 35 | G8.5 | 3 000 | M130 | 90 | 12 000 | 3 300 | 2 700 | U | Clear | Enclosed | 24 |
| 60107 | CMT35/U/935/G8.5 EYE | 35 | G8.5 | 3 500 | M130 | 90 | 12 000 | 3 300 | 2 400 | U | Clear | Enclosed | 24 |
| 58134 | CMT35/U/942/G8.5 EYE | 35 | G8.5 | 4 200 | M130 | 90 | 12 000 | 3 300 | 2 400 | U | Clear | Enclosed | 24 |
| 58135 | CMT70/U/930/G8.5 EYE | 70 | G8.5 | 3 000 | M139 | 90 | 15 000 | 7 200 | 5 900 | U | Clear | Enclosed | 24 |
| 58142 | CMT70/U/935/G8.5 EYE | 70 | G8.5 | 3 500 | M139 | 90 | 15 000 | 7 400 | 5 900 | U | Clear | Enclosed | 24 |
| 58136 | CMT70/U/942/G8.5 EYE | 70 | G8.5 | 4 200 | M139 | 94 | 12 000 | 7 400 | 5 900 | U | Clear | Enclosed | 24 |
| T6 | | | | | | | | | | | | | |
| 58129 | CMT35/U/830/G12 EYE | 35 | G12 | 3 000 | M130 | 83 | 12 000 | 3 300 | 2 700 | U | Clear | Enclosed | 24 |
| 60106 | CMT35/U/935/G12 EYE | 35 | G12 | 3 500 | M130 | 90 | 12 000 | 3 300 | 2 400 | U | Clear | Enclosed | 24 |
| 58130 | CMT35/U/942/G12 EYE | 35 | G12 | 4 200 | M130 | 90 | 12 000 | 3 300 | 2 400 | U | Clear | Enclosed | 24 |
| 58131 | CMT70/U/930/G12 EYE | 70 | G12 | 3 000 | M139 | 90 | 15 000 | 7 200 | 5 900 | U | Clear | Enclosed | 24 |
| 58143 | CMT70/U/935/G12 EYE | 70 | G12 | 3 500 | M139 | 90 | 15 000 | 7 400 | 5 900 | U | Clear | Enclosed | 24 |
| 58132 | CMT70/U/942/G12 EYE | 70 | G12 | 4 200 | M139 | 94 | 12 000 | 7 400 | 5 900 | U | Clear | Enclosed | 24 |
| 58125 | CMT150/U/832/G12 EYE | 150 | G12 | 3 200 | M142 | 87 | 12 000 | 15 000 | 12 300 | U | Clear | Enclosed | 24 |
| 58137 | CMT150/U/935/G12 EYE | 150 | G12 | 3 500 | M142 | 93 | 12 000 | 14 500 | 12 000 | U | Clear | Enclosed | 24 |
| 58126 | CMT150/U/942/G12 EYE | 150 | G12 | 4 200 | M142 | 93 | 12 000 | 14 500 | 12 000 | U | Clear | Enclosed | 24 |

