



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life ¹ (hrs)	Initial lumens ² (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable ³ (Yes/No)	Case qty
MR11													
MOL : 1 7/32 in. (38.5 mm) Dia. : 1 1/8 in. (35 mm)													
64244	LED/MR11/4W/30K/38/GU4/ND/STD	4	GU4	12	3 000	80	25 000	260	38	550	30	N	48
MR16*													
MOL : 1 7/8 in. (48 mm) Dia. : 1 3/8 in. (50 mm)													
62462	LED/MR16/6W/27K/25/STD	6	GU5.3	12	2 700	82	40 000	360	25	1 863	35	Y	24
62465	LED/MR16/6W/27K/38/STD	6	GU5.3	12	2 700	82	40 000	360	38	974	35	Y	24
62463	LED/MR16/6W/30K/25/STD	6	GU5.3	12	3 000	82	40 000	380	25	1 689	35	Y	24
62466	LED/MR16/6W/30K/38/STD	6	GU5.3	12	3 000	82	40 000	380	38	1 001	35	Y	24
62464	LED/MR16/6W/40K/25/STD	6	GU5.3	12	4 000	82	40 000	410	25	1 998	35	Y	24
62467	LED/MR16/6W/40K/38/STD	6	GU5.3	12	4 000	82	40 000	410	38	1 018	35	Y	24
63092	LED/MR16/7W/27K/25/STD	7	GU5.3	12	2 700	80	40 000	500	25	2 330	50	Y	24
63093	LED/MR16/7W/27K/38/STD	7	GU5.3	12	2 700	80	40 000	500	38	1 372	50	Y	24
63094	LED/MR16/7W/30K/25/STD	7	GU5.3	12	3 000	80	40 000	500	25	2 507	50	Y	24
63095	LED/MR16/7W/30K/38/STD	7	GU5.3	12	3 000	80	40 000	500	38	1 449	50	Y	24
63096	LED/MR16/7W/40K/25/STD	7	GU5.3	12	4 000	80	40 000	520	25	2 472	50	Y	24
63097	LED/MR16/7W/40K/38/STD	7	GU5.3	12	4 000	80	40 000	520	38	1 524	50	Y	24
63554	LED/MR16/7W/50K/38/STD	7	GU5.3	12	5 000	80	40 000	540	38	1 355	50	Y	24
MR16 - E26*													
MOL : 2 1/8 in. (54 mm) Dia. : 1 3/8 in. (50 mm)													
62433	LED/MR16E26/6W/NFL/30K/25/D/STD	6	E26	120	3 000	82	25 000	340	25	1 100	50	Y	48

Reflectors

MR16 - GU10



PAR16



PAR20



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life ¹ (hrs)	Initial lumens ² (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable ³ (Yes/No)	Case qty
MR16 - GU10*													
MOL : 2 3/32 in. (53 mm) Dia. : 1 3/32 in. (50 mm)													
62468	LED/GU10/6W/27K/25/STD	6	GU10	120	2 700	82	40 000	360	25	1 749	50	Y	24
62471	LED/GU10/6W/27K/38/STD	6	GU10	120	2 700	82	40 000	340	38	929	50	Y	24
62469	LED/GU10/6W/30K/25/STD	6	GU10	120	3 000	82	40 000	380	25	1 918	50	Y	24
62472	LED/GU10/6W/30K/38/STD	6	GU10	120	3 000	82	40 000	380	38	1 045	50	Y	24
62775	LED/GU10/6W/30K/38/STD/GRY	6	GU10	120	3 000	82	40 000	380	38	1 045	50	Y	24
62470	LED/GU10/6W/40K/25/STD	6	GU10	120	4 000	82	40 000	410	25	1 793	50	Y	24
62473	LED/GU10/6W/40K/38/STD	6	GU10	120	4 000	82	40 000	410	38	1 035	50	Y	24
63085	LED/GU10/7W/27K/25/STD	7	GU10	120	2 700	80	40 000	500	25	2 270	50	Y	24
63086	LED/GU10/7W/27K/38/STD	7	GU10	120	2 700	80	40 000	500	38	1 329	50	Y	24
63087	LED/GU10/7W/30K/25/STD	7	GU10	120	3 000	80	40 000	500	25	2 344	50	Y	24
63089	LED/GU10/7W/30K/38/STD	7	GU10	120	3 000	80	40 000	500	38	1 325	50	Y	24
63088	LED/GU10/7W/30K/38/STD/GRY	7	GU10	120	3 000	80	40 000	500	38	1 325	50	Y	24
63090	LED/GU10/7W/40K/25/STD	7	GU10	120	4 000	80	40 000	520	25	2 192	50	Y	24
63091	LED/GU10/7W/40K/38/STD	7	GU10	120	4 000	80	40 000	520	38	1 367	50	Y	24
63555	LED/GU10/7W/50K/38/STD	7	GU10	120	5 000	80	40 000	540	38	1 378	50	Y	24
PAR16*													
MOL : 3 3/32 in. (88 mm) Dia. : 1 3/32 in. (50 mm)													
62786	LED/P16/6W/30K/38/STD	6	E26	120	3 000	80	40 000	380	38	630	35	Y	24
PAR20**													
MOL : 3 3/8 in. (86 mm) Dia. : 2 5/32 in. (63 mm)													
63051	LED/P20/7W/27K/25/STD	7	E26	120	2 700	90	40 000	470	25	1 370	50	Y	12
63052	LED/P20/7W/27K/40/STD	7	E26	120	2 700	90	40 000	500	40	1 000	50	Y	12
63053	LED/P20/7W/30K/25/STD	7	E26	120	3 000	90	40 000	480	25	1 373	50	Y	12
63054	LED/P20/7W/30K/25/STD/BLK	7	E26	120	3 000	90	40 000	480	25	1 373	50	Y	12
63055	LED/P20/7W/30K/25/STD/GRY	7	E26	120	3 000	90	40 000	480	25	1 373	50	Y	12
63056	LED/P20/7W/30K/40/STD	7	E26	120	3 000	90	40 000	480	40	1 069	50	Y	12
63057	LED/P20/7W/40K/25/STD	7	E26	120	4 000	90	40 000	510	25	1 486	50	Y	12
63058	LED/P20/7W/40K/40/STD	7	E26	120	4 000	90	40 000	510	40	1 029	50	Y	12
63556	LED/P20/7W/50K/40/STD	7	E26	120	5 000	90	40 000	525	40	1 062	50	Y	12
62474	LED/PAR20/8W/NFL/27K/25/D/STD	8	E26	120	2 700	82	40 000	490	25	1 668	50	Y	12
62477	LED/PAR20/8W/FL/27K/40/D/STD	8	E26	120	2 700	82	40 000	490	40	759	50	Y	12
62475	LED/PAR20/8W/NFL/30K/25/D/STD	8	E26	120	3 000	82	40 000	500	25	1 710	50	Y	12
62580	LED/PAR20/8W/NFL/30K/25/D/STD/BLK	8	E26	120	3 000	82	40 000	500	25	1 710	50	Y	12
62773	LED/PAR20/8W/NFL/30K/25/D/STD/GRY	8	E26	120	3 000	82	40 000	500	25	1 710	50	Y	12
62478	LED/PAR20/8W/FL/30K/40/D/STD	8	E26	120	3 000	82	40 000	500	40	824	50	Y	12
62476	LED/PAR20/8W/NFL/40K/25/D/STD	8	E26	120	4 000	81	40 000	550	25	1 921	50	Y	12
62479	LED/PAR20/8W/FL/40K/40/D/STD	8	E26	120	4 000	81	40 000	550	40	909	50	Y	12



¹ Life rating based on L70 lumen depreciation design criteria. Average life of lamps that have been approved for ENERGY STAR early submission or complete submission can vary. ENERGY STAR early submission dictates that manufacturers can only claim 25 000 hour life with 3 000 hour actual life test data, 6 000 hour LM-80 data and in-situ temperature measurements. Once a product has been fully qualified, manufacturers may increase the lifetime of a product by demonstrating full compliance with the ENERGY STAR criteria at the new lifetime with Lumen Maintenance at the minimum required test period.

² Typical lumens +/- 5 %

³ For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com



PAR30SN



PAR30LN



PAR38

Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life ¹ (hrs)	Initial lumens ² (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable ³ (Yes/No)	Case qty
PAR30SN** ♦♦													
MOL: 3 13/32 in. (85 mm) Dia.: 3 3/4 in. (95 mm)													
63065	LED/P30S/10W/27K/25/STD	10	E26	120	2 700	90	40 000	780	25	3 230	75	Y	6
63066	LED/P30S/10W/27K/40/STD	10	E26	120	2 700	90	40 000	780	40	1 541	75	Y	6
63067	LED/P30S/10W/30K/25/STD	10	E26	120	3 000	90	40 000	820	25	3 240	75	Y	6
63068	LED/P30S/10W/30K/25/STD/BLK	10	E26	120	3 000	90	40 000	820	25	3 240	75	Y	6
63069	LED/P30S/10W/30K/40/STD	10	E26	120	3 000	90	40 000	820	40	1 581	75	Y	6
63070	LED/P30S/10W/40K/25/STD	10	E26	120	4 000	90	40 000	850	25	3 318	75	Y	6
63071	LED/P30S/10W/40K/40/STD	10	E26	120	4 000	90	40 000	850	40	1 680	75	Y	6
63558	LED/P30S/10W/50K/40/STD	10	E26	120	5 000	90	40 000	870	40	1 753	75	Y	6
62480*	LED/PAR30SN/14.5W/NFL/27K/25/D/STD	14.5	E26	120	2 700	81	40 000	850	25	3 078	75	Y	6
62483*	LED/PAR30SN/14.5W/FL/27K/40/D/STD	14.5	E26	120	2 700	81	40 000	850	40	1 403	75	Y	6
62481*	LED/PAR30SN/14.5W/NFL/30K/25/D/STD	14.5	E26	120	3 000	82	40 000	880	25	3 225	75	Y	6
62774*	LED/PAR30SN/14.5W/NFL/30K/25/D/STD/BLK	14.5	E26	120	3 000	82	40 000	880	25	3 225	75	Y	6
62484*	LED/PAR30SN/14.5W/FL/30K/40/D/STD	14.5	E26	120	3 000	82	40 000	850	40	1 341	75	Y	6
62482*	LED/PAR30SN/14.5W/NFL/40K/25/D/STD	14.5	E26	120	4 000	82	40 000	950	25	3 430	75	Y	6
62485*	LED/PAR30SN/14.5W/FL/40K/40/D/STD	14.5	E26	120	4 000	82	40 000	950	40	1 388	75	Y	6
PAR30LN** ♦♦													
MOL: 4 19/32 in. (117 mm) Dia.: 3 3/4 in. (95 mm)													
63059	LED/P30L/10W/27K/25/STD	10	E26	120	2 700	90	40 000	780	25	3 453	75	Y	6
63060	LED/P30L/10W/27K/40/STD	10	E26	120	2 700	90	40 000	780	40	1 452	75	Y	6
63061	LED/P30L/10W/30K/25/STD	10	E26	120	3 000	90	40 000	820	25	3 368	75	Y	6
63062	LED/P30L/10W/30K/40/STD	10	E26	120	3 000	90	40 000	820	40	1 575	75	Y	6
63063	LED/P30L/10W/40K/25/STD	10	E26	120	4 000	90	40 000	850	25	3 410	75	Y	6
63064	LED/P30L/10W/40K/40/STD	10	E26	120	4 000	90	40 000	850	40	1 590	75	Y	6
63557	LED/P30L/10W/50K/40/STD	10	E26	120	5 000	90	40 000	870	40	1 753	75	Y	6
62498	LED/PAR30LN/14W/NFL/27K/25/D/STD	14	E26	120	2 700	81	40 000	800	25	3 732	75	Y	6
62501	LED/PAR30LN/14W/FL/27K/40/D/STD	14	E26	120	2 700	81	40 000	850	40	1 448	75	Y	6
62499	LED/PAR30LN/14W/NFL/30K/25/D/STD	14	E26	120	3 000	82	40 000	880	25	3 771	75	Y	6
62502	LED/PAR30LN/14W/FL/30K/40/D/STD	14	E26	120	3 000	82	40 000	880	40	1 418	75	Y	6
62500	LED/PAR30LN/14W/NFL/40K/25/D/STD	14	E26	120	4 000	82	40 000	950	25	3 081	75	Y	6
62503	LED/PAR30LN/14W/FL/40K/40/D/STD	14	E26	120	4 000	82	40 000	950	40	1 585	75	Y	6

Reflectors

STANDARD's LED reflector lamps offer exceptional thermal management and professional grade optics to ensure uniform beam pattern, long life and luminous effect while reducing energy consumption.

Concise binning process ensures colour consistency from lamp to lamp. Ideal for goods and materials sensitive to heat and UV emission.



Order code	Description	Watts (W)	Base	Volts (VAC)	Colour temp. (K)	CRI	Average life ¹ (hrs)	Initial lumens ² (lm)	Beam angle (°)	CBCP (cd)	Traditional equivalent (W)	Dimmable ³ (Yes/No)	Case qty
PAR38** ♦♦													
MOL : 5 3/32 in. (129 mm) Dia. : 4 29/32 in. (120 mm)													
63072	LED/P38/15W/27K/25/STD	15	E26	120	2 700	90	40 000	980	25	5 403	100	Y	6
63073	LED/P38/15W/27K/40/STD	15	E26	120	2 700	90	40 000	980	40	2 164	100	Y	6
63074	LED/P38/15W/30K/25/STD	15	E26	120	3 000	90	40 000	1 050	25	5 378	100	Y	6
63075	LED/P38/15W/30K/40/STD	15	E26	120	3 000	90	40 000	1 050	40	2 119	100	Y	6
63076	LED/P38/15W/40K/25/STD	15	E26	120	4 000	90	40 000	1 100	25	5 540	100	Y	6
63077	LED/P38/15W/40K/40/STD	15	E26	120	4 000	90	40 000	1 100	40	2 263	100	Y	6
63559	LED/P38/15W/50K/40/STD	15	E26	120	5 000	90	40 000	1 150	40	1 397	100	Y	6
62504	LED/PAR38/16W/NFL/27K/25/D/STD	16	E26	120	2 700	81	40 000	980	25	4 727	90	Y	6
62507	LED/PAR38/16W/FL/27K/40/D/STD	16	E26	120	2 700	81	40 000	980	40	1 675	90	Y	6
62505	LED/PAR38/16W/NFL/30K/25/D/STD	16	E26	120	3 000	81	40 000	1 020	25	4 444	90	Y	6
62508	LED/PAR38/16W/FL/30K/40/D/STD	16	E26	120	3 000	81	40 000	1 020	40	1 683	90	Y	6
62506	LED/PAR38/16W/NFL/40K/25/D/STD	16	E26	120	4 000	81	40 000	1 150	25	4 766	90	Y	6
62509	LED/PAR38/16W/FL/40K/40/D/STD	16	E26	120	4 000	81	40 000	1 150	40	1 829	90	Y	6
63078	LED/P38/17W/27K/25/STD	17	E26	120	2 700	90	40 000	1 150	25	5 969	120	Y	6
63079	LED/P38/17W/27K/40/STD	17	E26	120	2 700	90	40 000	1 150	40	2 523	120	Y	6
63080	LED/P38/17W/30K/25/STD	17	E26	120	3 000	90	40 000	1 200	25	5 969	120	Y	6
63081	LED/P38/17W/30K/40/STD	17	E26	120	3 000	90	40 000	1 200	40	2 449	120	Y	6
63082	LED/P38/17W/40K/25/STD	17	E26	120	4 000	90	40 000	1 220	25	5 969	120	Y	6
63083	LED/P38/17W/40K/40/STD	17	E26	120	4 000	90	40 000	1 220	40	2 615	120	Y	6
R20* ♦													
MOL : 3 3/8 in. (86 mm) Dia. : 2 15/32 in. (63 mm)													
62784	LED/R20/7.5W/27K/STD	7.5	E26	120	2 700	82	40 000	500	40	759	50	Y	12
R20* ♦													
MOL : 3 29/32 in. (99 mm) Dia. : 2 25/32 in. (63 mm)													
62431	LED/R20/8W/27K/D/STD	8	E26	120	2 700	82	25 000	500	-	-	50	Y	48
BR30* ♦													
MOL : 5 29/32 in. (150 mm) Dia. : 4 1/16 in. (103 mm)													
63601	LED/BR30/9.5W/27K/STD	9.5	E26	120	2 700	81	25 000	650	120	218	65	Y	20
62783	LED/BR30/10W/27K/STD	10	E26	120	2 700	80	40 000	650	-	-	65	Y	6
BR40* ♦♦													
MOL : 6 1/4 in. (159 mm) Dia. : 4 29/32 in. (125 mm)													
63084	LED/BR40/17W/27K/STD	17	E26	120	2 700	80	40 000	1 100	100	401	85	Y	6
AR111* ♦													
MOL : 2 9/32 in. (58 mm) Dia. : 4 3/8 in. (111 mm)													
62630	LED/AR111/13W/FL/30K/12V/40/STD	13	G53	12	3 000	80	25 000	750	40	-	-	N	12



¹ Life rating based on L70 lumen depreciation design criteria. Average life of lamps that have been approved for ENERGY STAR early submission or complete submission can vary. ENERGY STAR early submission dictates that manufacturers can only claim 25 000 hour life with 3 000 hour actual life test data, 6 000 hour LM-80 data and in-situ temperature measurements. Once a product has been fully qualified, manufacturers may increase the lifetime of a product by demonstrating full compliance with the ENERGY STAR criteria at the new lifetime with Lumen Maintenance at the minimum required test period.

² Typical lumens +/- 5 %

³ For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com