Technical Information Bulletin

| Date: | |
|---------------------------|--|
| In hands date of project: | |
| Project name/Number: | |
| Name of distributor: | |
| Client #: | |
| Name of end user: | |

Diameter ΜĎ

Dia.: 1 31/32 in. (50 mm)

MOL: 2 5/32 in. (55 mm)

DAL06P, SAL06P, SLC03P, AAL06

IPL06, 6674, DSM10-1LZ

COMPATIBLE DIMMER LIST

CTCL-153P

HCL453P

Legrand

Cooper

Leviton

Lutron

ORDERING INFORMATION

Order code: 64416

Description: LED/GU10/6.5W/30K/25/STD

UPC: 69549644168

Case quantity: 24

PERFORMANCE DATA

MR16 Shape: Base: GU₁₀ 6.5 Wattage (W): Lamp voltage (VAC): 120 Colour temperature (K)**: 3 000 40 000 Average life (L70 hours): Initial lumens (lm)*: 574 Initial lumens per watt (lm/W): 88 CRI: 83 Beam angle (°): 25 CBCP: 2 504 Power factor: 0.86

Operating temperature range: - 40 °C / - 40 °F to 40 °C / 104 °F

**Typical colour temperature range: +/- 10 %





















CAUTIONS

- Turn power off before inspection, installation, or removal.
- Risk of electrical shock do not use where directly exposed to water or weather.
- · Not for use in totally enclosed luminaires. Suitable for use in damp locations.
- Do not open no user serviceable parts inside.
- Use only on 120 VAC, 60Hz circuits. • This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Compatible with most dimmers. • For complete dimmer and warranty information visit www.standardpro.com
- Not recommended for use with timers Operating temperature: -40 °C / -40 °F to 40°C / 104 °F
 5 Years Limited Warranty.

| Qty | Description | Price |
|-----|-------------|-------|
| | | |

I accept the specifications of the lamp configuration mentioned above. Name: Company:

Signature:

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.



Date: