Technical Information Bulletin

LED Lamps



Date:	Name of distributor:
In hands date of project:	Client #:
Project name / Number:	Name of and year

ORDERING INFORMATION

Order code: 65380

Description: LED/P20HO/7W/30K/35/STD

UPC: 69549653801

Case quantity: 50

PERFORMANCE DATA

Shape: **PAR20 E26** Base: E26 Wattage (W): Lamp voltage (VAC): 120 Colour temperature (K)**: 3 000 25 000 Average life (L70 hours): Initial lumens (lm)*: 660 Initial lumens per watt (lm/W): 94 CRI: 82 R9: 7 Beam angle (°): 35 CBCP: 1 374

Operating temperature range: -25°C/-13°F to 40°C/104°F

*Initial lumens range: +/- 10 %

Power factor:

**Typical colour temperature range: +/- 10 %

>0.8















CAN ICES-005 (B) / NMB-005 (B)

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.

CAUTIONS

- Turn power off before inspection, installation, or removal.
 Risk of electrical shock do not use where directly exposed to water or weather.
- · Not for use in totally enclosed luminaires.
- Suitable for use in damp locations.
 Do not open no user serviceable parts inside.
- Use only on 120 VAC, 60 Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Compatible with most dimmers.
- For complete dimmer and warranty information visit www.standardpro.com



COMPATIBLE DIMMERS

Legrand	HCL453P	
Cooper	AAL06, DAL06P, SLC03P	
Leviton	6615, 6674, DSL06-1LZ, IPE04-1LZ, IPL06	
Lutron	AYCL-253P, CTCL-153P, DVCL-153P, DVCL-253P, DVELV-300P, NTELV-600, SELV-300P	

Qty	Description	Price
I accept the spe	ecifications of the luminaire configuration n	entioned above.
Name:		
Company:		
Signature:		Date: