# Technical Information Bulletin



Nominal length : 48 in. (1 200 mm) Dia. : 1 in. (26 mm)

## Choice LED Linear \_\_

Date:	Name of distributor:	
In hands date of project:	Client #:	
Project name/Number:	Name of end user:	

## ORDERING INFORMATION

Order code: 67973

**Description:** 

T8/S2/10.5W/840/48/CHOICE/STD

UPC: 069549679733 DLC unique ID: PLN775ELHO0T

Case quantity:

## PHYSICAL DATA

Shape: T8 Base: G13 Material: Glass

## PERFORMANCE DATA

Bare Lamp Watts (W): 10.5

120 -277/347 Volts (VAC): Colour temperature (K)1: 4 000 Life L70 (hrs): 50 000 CRI: 82

Starting method: Instant start

-20°C/ -4°F to 40°C/104°F Operating temperature range:

Order code	Average System Watts (W)		Initial Lumens (Im) <sup>2</sup>			
	LBF	NBF	HBF <sup>3</sup>	LBF	NBF	HBF <sup>3</sup>
67977	11.5	13	17	1 600	1 800	2 400

<sup>&</sup>lt;sup>1</sup> Typical colour temperature range: +/- 5 %
<sup>2</sup> Lumen values are derived from photometric testing, Initial lumens range: +/- 10 %
<sup>3</sup> LBF= Low ballast factor, NBF= Normal ballast factor, HBF= High ballast factor













Please refer to the ballast compatibility list to confirm lamp compatibility with the existing luminaire.

## **CAUTIONS**

THIS LAMP OPERATES ON INSTANT START ELECTRONIC BALLASTS. Direct replacement for 32W/48 T8 only.

Qty		Description	Price				
I accept the specifications of the luminaire configuration mentioned above.							
Name:							
Company:							
Signature:			Date:				

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

