

Technical Information Bulletin

Choice LED Linear



Date: _____ Name of distributor: _____
 In hands date of project: _____ Client #: _____
 Project name/Number: _____ Name of end user: _____

ORDERING INFORMATION

Order code: 67977
Description: T8/S2/10.5W/850/48/CHOICE/STD
UPC: 069549679771
DLC unique ID: PLO98FNUUC36
Case quantity: 25



Nominal length : 48 in. (1 200 mm) Dia. : 1 in. (26 mm)

PHYSICAL DATA

Shape: T8
Base: G13
Material: Glass

PERFORMANCE DATA

Bare Lamp Watts (W): 10.5
Volts (VAC): 120 -277/347
Colour temperature (K)¹: 5 000
Life L70 (hrs): 50 000
CRI: 82
Starting method: Instant start
Operating temperature range: -20°C/ -4°F to 40°C/104°F

Order code	Average System Watts (W)			Initial Lumens (lm) ²		
	LBF	NBF	HBF ³	LBF	NBF	HBF ³
67977	11.5	13	17	1 600	1 800	2 400

¹ Typical colour temperature range: +/- 5 %
² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %
³ LBF= Low ballast factor, NBF= Normal ballast factor, HBF= High ballast factor



Please refer to the ballast compatibility list to confirm lamp compatibility with the existing luminaire.

CAUTIONS

THIS LAMP OPERATES ON INSTANT START ELECTRONIC BALLASTS.
 Direct replacement for 32W/48 T8 only.

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: _____
 Company: _____
 Signature: _____ Date: _____

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

