

RESETTABLE CIRCUIT BREAKER

LIGHTED ON/OFF POWER SWITCH

482.60 mm  
[19.000 in]

43.64 mm  
[1.718 in]

165.10 mm  
[6.500 in]

38.10 mm TYP  
[1.500 in]

76.20 mm TYP  
[3.000 in]

ASSEMBLY - VIEW FROM FRONT

19.05 mm  
[0.750 in]

444.50 mm  
[17.500 in]

5.08 mm  
[0.200 in]

67.58 mm  
[2.661 in]

15' FOOT  
POWER CORD  
(NEMA 5-15P)

ASSEMBLY - VIEW FROM BOTTOM

10.31 mm  
[0.406 in]

461.98 mm  
[18.188 in]


5.97 mm  
[0.235 in]

31.70 mm  
[1.248 in]


127.00 mm  
[5.000 in]

SECTION A-A

R3.18 mm  
[0.125 in]



ISOMETRIC VIEW



40.46 mm  
[1.593 in]

ASSEMBLY - VIEW FROM SIDE

1582H6B1BK

Finish - Front - Black Painted Steel

Back - Black Painted Steel

Rated - 125 VAC, 60 Hz, 15 Amps

Approvals - CSA Certified Standards C22.2 (No. 21-95, 42-99)

- UL Recognized Standard UL1363



HAMMOND  
MANUFACTURING™

1582H6B1BK

www.hammondmfg.com