

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

				ALL DIMENSION	SAREIN mm				
Part Number	Class 2r Wire Size	Class 5f & 6f Wire Size	Wire Strip Length 16.5	Panduit Die Index No. For Class 2r Wire Circumferential Dies	Panduit Die Index No. For Class 5f & 6f Wire Circumferential Dies	Panduit Die hdex No. For Class 5f & 6f Wire Nest/Indentor Dies 	l ±2.76 30.0	o ±.50 6.20	i ±.50 4.50
SCMS10-C	10mm ²			P21					
SCMS16-C	16mm ²	10mm ²	19.0	P24	P21	P29/1	35.0	7.20	5.50
SCMS25-L	25mm ²	16mm ²	19.5	P29	P21	P29/1	36.0	8.80	6.90
SCMS35-L	35mm ²	25mm ²	19.5	P29	P29	P42/2	36.0	10.40	8.20
SCMS50-L	50mm ²	35mm ²	26.0	P37	P33	P50/2	49.0	12.30	9.80
SCMS70-L	70mm ²	50mm ²	27.5	P45	P37	P50/2	52.0	14.20	11.5
SCMS95-Q	95mm ²	70mm ²	28.5	P54	P45	P62/4	54.0	16.50	13.5
SCMS120-Q	120mm ²	95mm ²	30.0	P62	P50	P76/4	57.0	18.60	15.2
SCMS150-X	150mm ²	120mm ²	30.0	P66		P76/4	57.0	21.00	16.5
SCMS185-X	185mm ²	150mm ²	32.0	P76		P76/4	61.0	23.00	18.6
SCMS240-X	240mm ²	185mm ²	37.5	P87		P87/4	72.0	26.00	20.8
SCMS300-5	300mm ²	240mm ²	39.0	P94		P106/6	75.0	29.00	23.5
SCMSX300-5		300mm ² 5f ONLY	49.0			P32/6	95.0	33.00	26.2
SCMS400-5	400mm ²		49.0	P106			95.0	34.50	27.0
SCMS500-6	500mm ²		49.5	P125			96.0	40.00	31.0
SCMS630-6	630mm ²		67.0	P125			131.0	44.00	34.5

NOTES:

- 1. Material: High conductivity seamless copper tube.
- 2. Plating: Parts are annealed and tin plated.
- 4. UL Listed Wire Connector: Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instruction with applications greater than 2000 volts.
- 5. UL Temperature Rating: 90° C
- 6. C.S.A. Certified Wire Connector: Yes
- 7. Parts are CE and tested per EN 61238-1:2003/IEC 61238-1:2003 Class B, with Class 2r wire 10mm² 630mm².





							METRIC SPLICES - SCMS SERIES 10-630mm CUSTOMER DRAWING
							ITEM REVISION NAME 13J059BI/02
							DATASET FILE NAME 13J059BI-JC/02.SLDDRW
00	7/14		TICO				
02	7/14	JHNU	ILCO	RGB	ADDED 5f ONLY TO WIRE SIZE FOR SCMSX300 PART	13J059BI-JC	DIMENSIONAL TOLERANCES ARE: IN [mm]
01	6/14	JHNU	TLCO	RGB	REVISED NOTE 7: 630 WAS 240	13J059BI-JC	.X ± .XX ± SEE NOTES .XX ± ANGLES ±
00	6/14	JHNU	TLCO	RGB	DRAWING RELEASED	13J059BI-JC	THIRD ANGLE DRAWING NUMBER 12J059BI-JC
REV	DATE	BY	СНК	APR	DESCRIPTION	ECN	DRAWN BY DATE CHK SCALE SHEET 1 OF 1 SIZE JHNU 6/14 TLCO NONE SHEET 1 OF 1 B

3. Wire Type: Class 2r, 5f & 6f Stranded Copper per DIN VDE 0295, IEC 60228 and HD 383.



