



Quality Products. Service Excellence.

Type 4 Two Door Freestanding Enclosure *HN4 FSTD Series*

Continuous Hinge Door with Handle



Panel Sold Separately



Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications.

Construction

- Formed 12 gauge steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Heavy duty stainless steel lifting eyebolts are provided with reinforcing support angles.
- Doors are supported with heavy gauge continuous hinges.
- Dual Access versions have doors front and back.
- 3-pt padlocking door handle.
- Seamless poured-in place gasket.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.
- Center post is removable for easy installation of the inner panel.

Standards

- UL 508A Type 3R, 4 and 12
- CSA Type 3R, 4 and 12
- Complies with:
 - NEMA Type 3R, 4, 12 and 13
 - IEC 60529, IP66

Finish

- Cover and enclosure are finished in recoatable smooth ANSI 61 gray powder coating.
- Optional inner panels are available in white powder coating, or unpainted galvanized steel.

Accessories

- Inner Panels
- Panel Rails
- Door Stop Kit
- Drip Shield Kit
- Window Kits
- Lighting
- Center Panel Supports
- Swing Out Frames
- Top Hat Cable Modules
- Type 12/4, 4X Handle Kits
- Climate Control
- General Accessories

Single Access

| Part No. | Enclosure | | | Optional Full Panel ¹ |
|-------------|-----------|-------|-------|----------------------------------|
| | H | W | D | |
| HN4FS604818 | 60.00 | 48.00 | 18.00 | 60AWFW |
| HN4FS724818 | 72.00 | 48.00 | 18.00 | 72ZFW |

| Part No. | Enclosure | | | Optional Full Panel ¹ |
|-------------|-----------|-------|-------|----------------------------------|
| | H | W | D | |
| HN4FS726018 | 72.00 | 60.00 | 18.00 | 72ZXFW |
| HN4FS727218 | 72.00 | 72.00 | 18.00 | 72ZYFW |
| HN4FS904820 | 90.00 | 48.00 | 20.00 | 90BWFW |
| HN4FS907220 | 90.00 | 72.00 | 20.00 | 90BYFW |
| HN4FS724824 | 72.00 | 48.00 | 24.00 | 72ZWFW |
| HN4FS726024 | 72.00 | 60.00 | 24.00 | 72ZXFW |
| HN4FS727224 | 72.00 | 72.00 | 24.00 | 72ZYFW |
| HN4FS907224 | 90.00 | 72.00 | 24.00 | 90BYFW |
| HN4FS726036 | 72.00 | 60.00 | 36.00 | 72ZXFW |
| HN4FS907236 | 90.00 | 72.00 | 36.00 | 90BYFW |

¹ Refers to optional full height/full width panels. Depth panels/half height width panels are also available

Dual Access

| Part No. | Enclosure | | | Optional Full Panel ¹ |
|---------------|-----------|-------|-------|----------------------------------|
| | H | W | D | |
| HN4FS724824DA | 72.00 | 48.00 | 24.00 | 72ZWFW |
| HN4FS726024DA | 72.00 | 60.00 | 24.00 | 72ZXFW |
| HN4FS727224DA | 72.00 | 72.00 | 24.00 | 72ZYFW |
| HN4FS907224DA | 90.00 | 72.00 | 24.00 | 90BYFW |
| HN4FS726036DA | 72.00 | 60.00 | 36.00 | 72ZXFW |

¹ Refers to optional full height/full width panels. Depth panels/half height width panels are also available

Data subject to change without notice

© 2021. Hammond Manufacturing Ltd. All rights reserved.