SATCO NUVO

Project Name

Location Prepared By



SATCO S39391

22W/LED/HID/5000K/100-277V E26

Notes

[www] 11-22-2021 02:57:4

Compliance

General	
Status	Active
Watts	22W
Incandescent Equivalent	150W
Fluorescent Equivalent	40W
HID Equivalent	100W
Volts	100V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	80
Lumens	3080L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 8.5 in. Width: 6 in. Depth: 6 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
	A C 00 005V
Working Voltage	AC 90-305V
Working Voltage Operating Frequency	50/60 Hz
Working Voltage Operating Frequency Power Factor	50/60 Hz >0.9
Working Voltage Operating Frequency Power Factor Burning Position	50/60 Hz >0.9 Universal
Working Voltage Operating Frequency Power Factor	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV
Working Voltage Operating Frequency Power Factor Burning Position	50/60 Hz >0.9 Universal
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C (+113F)
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C (+113F) 5.69
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C (+113F) 5.69 2.38
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C (+113F) 5.69 2.38 Plastic (PS)
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C (+113F) 5.69 2.38 Plastic (PS) Plastic (PS)
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C (+113F) 5.69 2.38 Plastic (PS)
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C (+113F) 5.69 2.38 Plastic (PS) Plastic (PS) White
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C (+113F) 5.69 2.38 Plastic (PS) Plastic (PS) White
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C (+113F) 5.69 2.38 Plastic (PS) Plastic (PS) White
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C (+113F) 5.69 2.38 Plastic (PS) Plastic (PS) White 0.68 UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C (+113F) 5.69 2.38 Plastic (PS) Plastic (PS) White 0.68 UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg)
Working Voltage Operating Frequency Power Factor Burning Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	50/60 Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to a maximum of +45C (+113F) 5.69 2.38 Plastic (PS) Plastic (PS) White 0.68 UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes

Safety Listing	cULus
Location Rating	Damp
Energy Star	No
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: http://www.satco.com/







