

## Rigid IMC

### Universal Super Fitting™ 3 Piece Coupling

#### Applications

- Used to join two lengths of conduit; couples conduit when conduit cannot be turned
- Threaded GRC/IMC to Threaded GRC/IMC
- Threaded GRC/IMC to Unthreaded GRC/IMC
- Threaded GRC/IMC to PVC
- Threaded GRC/IMC to Thin Wall EMT (2½" to 4")

#### Features

- UL Concrete-tight
- Ease of installation/Quick-connect
- Universal connecting - Threaded to Threaded, Threaded to Unthreaded
- No more turning Pipe
- Self Pipe Alignment
- Eliminates field threading
- Fit GRC/IMC/EMT (Fits all UL approved metal conduit)
- Fit PVC Schedule 40 and Schedule 80
- Lightweight

#### Standard Materials

- Steel

#### Standard Finish

- Zinc plated


#### Applicable Third Party Standards

- UL us listed UL 514B; C22.2 No. 18.3-12
- UL Listed File # E207875

#### U.S. Patent No. 8.586.881



Threaded GRC / IMC to Threaded GRC / IMC



Threaded GRC / IMC to Unthreaded GRC / IMC / EMT / PVC



Catalog Number	Replaces Part Number	Trade Size (in)	Dim A (in)	Dim B (in)	Inner Pack	Master Pack	Weight Per C (lb)
SEC50KON*	EC50KON	½	1.56	1.25	25	100	20
SEC75KON*	EC75KON	¾	1.62	1.45	25	100	23
SEC100KON*	EC100KON	1	1.96	1.71	10	50	36
SEC125KON*	EC125KON	1¼	2.08	2.07	5	25	46
SEC150KON*	EC150KON	1½	2.12	2.32	5	25	55
SEC200KON*	EC200KON	2	2.19	2.80	2	10	70
SEC250KON**	EC250KON	2½	3.19	3.45	2	-	170
SEC300KON**	EC300KON	3	3.31	4.08	1	-	210
SEC350KON**	EC350KON	3½	3.55	4.59	1	-	270
SEC400KON**	EC400KON	4	3.92	5.24	1	-	370
SEC500KON*	EC500KON	5	5.38	6.25	1	-	538

\* Use with Rigid and IMC

\*\* Use with Rigid, IMC, EMT and PVC