



YC4C4

by Burndy Catalog ID: YC4C4

Prop 65 Notice

CU Compression C Shape Compression Connector, 600 Volts to 35 Kv, 6 Sol. - 4 Str. (Run & Tap).

Features: Range-Taking Connector: Lowers Inventory Requirements, Compact Size: Easy To Tape And Insulate Connection, Manufactured From High Conductivity Wrought Copper: Provides Low Resistance And Excellent Electrical Conductivity, Economical: Provides Low Installed Cost, Conductor Size (run - Range): 6 AWG Solid - 4 AWG Stranded, Conductor Type: Run And Tap: Commercial Stranded Copper, Conductor Size (tap Range): 14 - 8 AWG Flex Copper, Shape: C, Die Index: BG Or 5/8 Element A, Tools, Die Set Catalog Number, And (number Of Crimps): Y35, Y750, Y45, Y46 Tool, U-BG Die, (1), MD6 Tool, BG Die, (2), W-BG Die, (1), OUR840 Tool, XNBG Die, (2)

Product Details

General

Application	For Range Of Copper And Making Tap Or Parallel Copper Connections
Die Index	BG or 5/8
Material	Copper
Plated	N
Plating Type	Unplated
Sub Brand	CRIMPIT
Trade Name	CRIMPIT™
Туре	YC-C Series
UPC	781810113509
UPC 12 Digit	7818101135099

Dimensions

Dimension - Height inch	0.81 in
Dimension - L Length Overall mm	14 mm
Dimension - Length Overall inch	0.57 in

Conductor Related

Conductor - Copper Solid Run Range	6 Sol 4 Str.
Conductor - Copper Solid Tap Range	6 Sol 4 Str.
Conductor - Copper Str Run Range	6 Sol 4 Str.
Conductor - Copper Str Tap	4 AWG
Conductor Type	Cu C Sol-Size

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No

Certification - cULus	No
Industry Standard(s)	• UL 486A • UL486B
Standards - Industry Standards Met	• UL 486A • UL486B
Standards - RoHS Compliance Status	СМ
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days

Phone: 1-800-346-4175

1-603-647-5299 (International)