

H-MOSS® Controls Count Down Timer Wall Switch Timers

HUBBELL

Features

- 30 minute timer
- Pre-set 5 button selection with permanent time markings
- Manual override to OFF
- Alert to OFF function - red LED will flash during the final 30 seconds
- Designed for use on 120 or 277V AC circuits



Ordering Information

Description	UPC Number	Catalog Number
Count down timer wall switch; settings: OFF, 5, 10, 20, 30 minutes	783585256412	DT5030W

Listings

cULus listed to UL60730-1 and UL60730-2
Meets ASHRAE 90.1, and CEC Title 24 compliant

Specifications

Housing	Polycarbonate
Mounting Bracket	Aluminum
Wire Leads	6" 14AWG copper wire
Mounting Strap	Steel

Performance

Controls


5 button selection	Preset time selection
LED Indicators	Illuminates once time is selected
OFF Switch	Manual override to OFF

Electrical

Load Capacity	120V AC - 8.3A, Resistive or Inductive (1000W Incandescent), 1/6 hp. 277V AC - 5.1A, Inductive (1400W Fluorescent)
---------------	--

Environmental

Operating Temperature	32°F to 122°F (0°C to 50°C) with rate of change not exceeding 20°F(11°C) per hour
Storage	-40°F to 150°F (-40°C to 65°C); 20% to 90% non condensing relative humidity



Complementary Products

Nylon Wallplate	NP26W
SS Wallplate	SS26
Snap-On Wallplate	RCW1W

Online Resources

Customer Use Drawing
eCatalog
Installation Instructions

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

