## SIEMENS

## Data sheet

## 6GK5108-0BA00-2AA3



\*\*\*\*\*\* Replacement part \*\*\*\*\*\* SCALANCE X108, Unmanaged IE switch, 8x 10/100 Mbit/s RJ45 ports, LED diagnostics, error-signaling contact with set button, redundant Power supply Manual available as a download

product type designation	SCALANCE X108
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
<ul> <li>for network components or terminal equipment</li> </ul>	8; RJ45 with securing collar
number of 100 Mbit/s SC ports	
for multimode	0
interfaces / other	
number of electrical connections	
<ul> <li>for signaling contact</li> </ul>	1
• for power supply	1
type of electrical connection	
<ul> <li>for signaling contact</li> </ul>	2-pole terminal block
<ul> <li>for power supply</li> </ul>	4-pole terminal block
signal inputs/outputs	
operating voltage / of the signaling contacts	
at DC / rated value	24 V
operational current / of the signaling contacts	
• at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
<ul> <li>supply voltage / 1 / rated value</li> </ul>	24 V
<ul> <li>power loss [W] / 1 / rated value</li> </ul>	3.36 W
<ul> <li>supply voltage / 1 / rated value</li> </ul>	18 32 V
<ul> <li>consumed current / 1 / maximum</li> </ul>	0.14 A
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	4-pole terminal block
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes
ambient conditions	
ambient temperature	
<ul> <li>during operation</li> </ul>	-20 +70 °C
<ul> <li>during storage</li> </ul>	-40 +80 °C
during transport	-40 +80 °C
relative humidity	
<ul> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP30

design, dimensions and weights	
design	compact
width	60 mm
height	125 mm
depth	124 mm
net weight	0.78 kg
fastening method	
<ul> <li>35 mm top hat DIN rail mounting</li> </ul>	Yes
<ul> <li>wall mounting</li> </ul>	Yes
<ul> <li>S7-300 rail mounting</li> </ul>	Yes
<ul> <li>S7-1500 rail mounting</li> </ul>	No
product functions / management, configuration, engineeri product function	ng
• multiport mirroring	No
• CoS	Yes
product function / switch-managed	No
product functions / redundancy	
product function	
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
<ul> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No
standards, specifications, approvals	
standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4A, Class 1, Zone 2, Group IIC, T4
<ul> <li>for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-1
<ul> <li>for emitted interference</li> </ul>	EN 61000-6-4 (Class A)
<ul> <li>for interference immunity</li> </ul>	EN 61000-6-2
MTBF	139.83 у
reference code	
<ul> <li>acc. to IEC 81346-2</li> </ul>	KF
<ul> <li>according to IEC 81346-2:2019</li> </ul>	KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environn	nents
standard / for hazardous zone	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X
<ul> <li>from CSA and UL</li> </ul>	UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T, Class 1 / Zone 2 / Group IIC / T
standards, specifications, approvals / other	
certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes
<ul> <li>KC approval</li> </ul>	Yes
● E1 approval	Yes
• E1 approval	Yes
<ul> <li>railway application in accordance with EN 50155</li> </ul>	No
standards, specifications, approvals / marine classification	n
Marine classification association	
<ul> <li>American Bureau of Shipping Europe Ltd. (ABS)</li> </ul>	Yes
<ul> <li>French marine classification society (BV)</li> </ul>	Yes
<ul> <li>Det Norske Veritas (DNV)</li> </ul>	No
Germanische Lloyd (GL)	No
DNV GL	Yes
<ul> <li>Lloyds Register of Shipping (LRS)</li> </ul>	Yes
<ul> <li>Nippon Kaiji Kyokai (NK)</li> </ul>	Yes
<ul> <li>Polski Rejestr Statkow (PRS)</li> </ul>	Yes
<ul> <li>Royal Institution of Naval Architects (RINA)</li> </ul>	Yes
further information / internet-Links	
Internet-Link	

<ul> <li>to web page: selection aid TIA Selection Tool</li> </ul>	http://www.siemens.com/tia-selection-tool
<ul> <li>to website: Industrial communication</li> </ul>	http://www.siemens.com/simatic-net
<ul> <li>to website: Industry Mall</li> </ul>	https://mall.industry.siemens.com
<ul> <li>to website: Information and Download Center</li> </ul>	http://www.siemens.com/industry/infocenter
<ul> <li>to website: Image database</li> </ul>	http://automation.siemens.com/bilddb
<ul> <li>to website: CAx-Download-Manager</li> </ul>	http://www.siemens.com/cax
<ul> <li>to website: Industry Online Support</li> </ul>	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

11/6/2021 🖸