

T5

SNF Ordering Information for T5

SAMPLE NUMBER: SNF-228T5-UNV-EBT1-U

Tandem Blank =2' or 4' Length 8T =8' Length	Number of Lamps 1 =1 Lamp 2 =2 Lamp (Not Included)	Voltage ⁽¹⁾ 120V =120 Volt 277V =277 Volt 347V =347 Volt UNV =Universal Voltage 120-277	Ballast Type ^{(1), (4)} EBT = T5 or T5HO Linear Electronic Program Rapid Start. Total Harmonic Distortion < 10% No. of Ballast 1 or 2 Ballast Factor/Type (For 28WT5 and 14WT5 Lamps Only) N =Normal Light Output .95 BF ⁽¹⁾ H =High Light Output 1.15 BF ^{(1), (6)} NDIM =Normal .95-1.0 BF Step Dimming ⁽⁷⁾ HDIM =High 1.15 BF Step Dimming ^{(6), (7)}	Options ⁽²⁾ RIF1 =Radio Interference Suppressor 6-3/18 SJT-C&P-515P =Cord & Plug (120V)(15 AMP) ⁽⁵⁾ 6-3/18 SJT-C&P L715P = Cord & Plug (277V)(15 AMP) ⁽⁵⁾ PI/CPI =Plug-In Option ⁽⁵⁾
Series SNF =Commercial Narrow Striplite	Wattage 14T5 =14WT5 (24") 24T5 =24WT5HO (24") 28T5 =28WT5 (48") 54T5 =54WT5HO (48")	Options GL =Single Element Fuse GM =Double Element Fuse EL5 =Emergency Installed ^{(3), (4)} EL5HO =Emergency Installed for T5HO	Packaging U =Unit Pack 6B =6 Bulk Packing (96")	

NOTES: ⁽¹⁾Products also available in non-US voltages and frequencies for international markets. Voltage must be specified when ordered with plugs or emergency ballast. ⁽²⁾For SilverLining reflector add SS in Catalog Number, Example: SNF-ASY-SS-4T5. ⁽³⁾Not available for 2' version. ⁽⁴⁾Maximum width clearance for ballast in channel is 2-7/32". ⁽⁵⁾Socket brackets left uninstalled. ⁽⁶⁾1-Lamp ballast in the High Ballast factor not available. 2-Lamp ballast will not operate 1-Lamp. ⁽⁷⁾Step Dimming ballast available for 28WT5 and 14WT5 lamps only.

Specifications & dimensions subject to change without notice. Consult your Cooper Lighting Representative for availability and ordering information.

ACCESSORIES (Order Separately)

- AYC-Chain/Set**=36" Chain Hanger (Use 1 Set Per Fixture)
- SCF**=Fixed Stem Set (Specify Length)
- SCS**=Swivel Stem Set (Specify Length)
- SCA**=Adjustable 48" Stem Set
- EYE CHAIN SET/3FT**=Eye Bolt Chain (Use 1 Set Per Fixture)
- SNF-ASY-3**=3" Asymmetric Reflector (Specify Length)
- SNF-SYM-3**=6" Symmetric Reflector (Specify Length)
- SNF-REV-3**=Reverse Asymmetric Reflector
- WG/SNFT5-4FT**=Wire Guard
- A1B/Spacer-U**=Spacer 1-1/2" to 2-1/2" from ceiling (Use 2 Per Fixture)
- TOGGLE**=Single Toggle NO. 2 (Specify Length)
- Y-TOGGLE**=Y Toggle NO. 2 (Specify Length)



narrow striplite