

# GROUNDING

## Ground Rods (Copper Bonded)



- ◆ Heavy uniform covering of electrolytic copper
- ◆ Corrosion resistant
- ◆ Easy Driving
- ◆ Bronze connectors should be used with copper bonded ground rods


Cat. No	Dia. Inches	Length Feet	Shipping Wt. lbs (100 pcs)	Std. Pkg
<b>K62-7</b>	1/2	7	440	5
<b>K62-8</b>	1/2	8	505	5
<b>K63-6</b>	5/8	6	575	5
<b>K63-8</b>	5/8	8	765	5
<b>K63-10</b>	5/8	10	955	5
<b>K64-6</b>	3/4	6	855	5
<b>K64-8</b>	3/4	8	1140	5
<b>K64-10</b>	3/4	10	1425	5

## Ground Rod Connectors (Bronze)

Cat. No	Rod Dia. Inches	Wire Range Max. Min.	Thread Size UNC-2A	Shipping Wt. lbs (100 pcs)	Std. Pkg
<b>K56-58</b>	5/8	1/0 Str. 8 Sol.	7/16-14	29	50
<b>K56-34</b>	3/4	1/0 Str. 8	7/16-14	33	100



- ◆ Non ferrous casting with clamping screw which clamps ground wire to copper bonded ground rod
- ◆ Floating pressure bar distributes pressure evenly over large area of ground bar



## Ground Plate

Cat No.	Shipping Wt. lbs (100 pcs)	Std. Pkg
<b>K61-56</b>	1100	1

- ◆ Complete with 3/4" Ground Rod Connection Post
- ◆ Hot dip galvanized
- ◆ 5/8" post available upon request
- ◆ Ground Rod Clamp not included. Order separately. Cat No. K56-1, K56-2 or K56-34