

ANCHORS & GUYING

Screw Anchor



Cat. No.	Blade Dia. Inches	Rod Dia. Inches	Rod Length Feet	Approx Strength Dry Clay	Shipping Wt. lbs (100 pcs)	Std. Pkg
K151-6	6	3/4	5-1/2	5000 lbs	1050	5
K151-8	8	1	5-1/2	8000 lbs	1500	2

- ◆ C.S.A. standard
- ◆ Large forged rod eye to take 1" bar for hand installation
- ◆ Chisel point is provided to aid installation
- ◆ Blade pitched to bite correctly into soil without undue earth disturbance
- ◆ Hot dip galvanized

Power Installed Screw Anchors

Cat No.	Helix Inches	Tapped Inches	Shipping Wt. lbs (100 pcs)	Std. Pkg
K156-2	8	1	1000	5
K156-5	10	1	1300	4
K156-13	12	1	1330	3

1 3/8" Hub

- ◆ Rated at 6,000 ft lb torque
- ◆ Tapped hub for 5/8"-11 threads available

Cat No.	Helix Inches	Tapped Inches	Shipping Wt. lbs (100 pcs)	Std. Pkg
K156-8	8	1	1100	5
K156-10	10	1	1400	4
K156-12	12	1	1600	2

1 1/2" Hub

- ◆ Rated at 8,000 ft lb torque
- ◆ Tapped hub for 5/8"-11 threads available



Heavy Duty Power Installed Screw Anchors

Cat No.	Helix Inches	Tapped Inches	Shipping Wt. lbs (100 pcs)	Std. Pkg
K156-108	8	1	1100	5
K156-110	10	1	1300	4
K156-112	12	1	1500	2
K156-114	14	1	2000	2



- ◆ Rated at 10,000 ft lb torque
- ◆ Universal hub - 1 1/2" or 1 3/8" drive shaft