


INSULATOR HARDWARE

Bolt Head Clevis

Cat No.	Shipping Wt. lbs (100 pcs)	Std. Pkg
K36-1	188	25

- ◆ Used for deadending on crossarms and poles
- ◆ Formed steel
- ◆ Hot dip galvanized



Dead End Clevis


- ◆ C.S.A. standard
- ◆ Formed from 1/4" x 1 1/2" high grade steel bar
- ◆ Used to dead end insulator assemblies
- ◆ Hot dip galvanized

Cat No.	Shipping Wt. lbs (100 pcs)	Std. Pkg
K36-2	152	50

Thimble Clevises

Cat No.	Cotter Bolt Dia. Inches	Thimble Dia. Inches	Max. Strand Dia. Inches	Rating lbs	Shipping Wt. lbs (100 pcs)	Std. Pkg
K271**	5/8	1-3/4	7/8	22,500	179	25
K270-1*	5/8	2-3/4	1-3/8	10,000	152	25
K270-2*	5/8	2-3/4	7/8	22,500	300	25

- ◆ For dead ending wire or strand to suspension insulators
- ◆ Smooth groove eliminates chafing of soft strand
- ◆ Large thimble diameter to maintain strand shape
- ◆ Takes hook for stringing and tensioning
- ◆ **K271 - malleable casting steel bolt, steel cotter key
- ◆ *K270 - formed steel
- ◆ Ferrous parts hot dip galvanized



K270



K271

Sky Hook (Pulling Hook)



Cat No.	Rating lbs	Shipping Wt. lbs (100 pcs)	Std. Pkg
K270-10	6000	120	25

- ◆ For connecting preform deadend clamp to a line puller to sag the conductor prior to installation of the preform grip
- ◆ Heat treated steel
- ◆ Hot dip galvanized