



A-Shape LED

Dimensional drawing



Product	D	C
16A19/PER/940/P/E26/DIM 6/1FB T20	60 mm	112 mm
16A19/PER/950/P/E26/DIM 6/1FB T20	60 mm	112 mm
16A19/PER/927/P/E26/DIM 6/1FB T20	60 mm	112 mm
16A19/PER/930/P/E26/DIM 6/1FB T20	60 mm	112 mm

Product	D	C
8.5A19/LED/927/FR/P/ND 4/1FB	60 mm	104 mm
8.5A19/LED/930/FR/P/ND 4/1FB	60 mm	104 mm
8.5A19/LED/950/FR/P/ND 4/1FB	60 mm	104 mm

Operating and electrical

Voltage (Nom)	120 V
Starting Time (Nom)	0.5 s

Light technical

Llmf At End Of Nominal Lifetime (Nom)	70 %
---------------------------------------	------

Approval and application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
549485	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	- kWh
549493	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	- kWh
545897	8.8A19/PER/940/P/E26/DIM 6/1FB T20	- kWh
550400	5A19/PER/927/P/E26/DIM 6/1FB T20	- kWh
550418	5A19/PER/930/P/E26/DIM 6/1FB T20	- kWh
547042	5A19/PER/940/P/E26/DIM 6/1FB T20	- kWh
550426	5A19/PER/950/P/E26/DIM 6/1FB T20	- kWh
550434	8.8A19/PER/927/P/E26/DIM 6/1FB T20	- kWh
550442	8.8A19/PER/930/P/E26/DIM 6/1FB T20	- kWh
550459	8.8A19/PER/950/P/E26/DIM 6/1FB T20	- kWh

Order Code	Full Product Name	Energy Consumption kWh/1000 h
554485	16.6A21/LED/950/P/E26/ND 6/1FB T20	- kWh
558239	29A21/PER/850/P/E26/DIM/HO 4/1FB	-
561019	16A19/PER/950/P/E26/DIM 6/1FB T20	- kWh
561068	16A19/PER/927/P/E26/DIM 6/1FB T20	- kWh
561076	16A19/PER/930/P/E26/DIM 6/1FB T20	- kWh
561456	16A19/PER/940/P/E26/DIM 6/1FB T20	- kWh
557660	8.8A19/PER/930/P/GU24/DIM 6/1FB T20	-
565119	8.5A19/LED/927/FR/P/ND 4/1FB	-
565127	8.5A19/LED/930/FR/P/ND 4/1FB	-
565135	8.5A19/LED/950/FR/P/ND 4/1FB	-

Controls and dimming

A-Shape LED

Order Code	Full Product Name	Dimmable
549485	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	Yes
549493	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	Yes
545897	8.8A19/PER/940/P/E26/DIM 6/1FB T20	Yes
550400	5A19/PER/927/P/E26/DIM 6/1FB T20	Yes
550418	5A19/PER/930/P/E26/DIM 6/1FB T20	Yes
547042	5A19/PER/940/P/E26/DIM 6/1FB T20	Yes
550426	5A19/PER/950/P/E26/DIM 6/1FB T20	Yes
550434	8.8A19/PER/927/P/E26/DIM 6/1FB T20	Yes
550442	8.8A19/PER/930/P/E26/DIM 6/1FB T20	Yes
550459	8.8A19/PER/950/P/E26/DIM 6/1FB T20	Yes

Order Code	Full Product Name	Dimmable
554485	16.6A21/LED/950/P/E26/ND 6/1FB T20	No
558239	29A21/PER/850/P/E26/DIM/HO 4/1FB	Yes
561019	16A19/PER/950/P/E26/DIM 6/1FB T20	Yes
561068	16A19/PER/927/P/E26/DIM 6/1FB T20	Yes
561076	16A19/PER/930/P/E26/DIM 6/1FB T20	Yes
561456	16A19/PER/940/P/E26/DIM 6/1FB T20	Yes
557660	8.8A19/PER/930/P/GU24/DIM 6/1FB T20	Yes
565119	8.5A19/LED/927/FR/P/ND 4/1FB	No
565127	8.5A19/LED/930/FR/P/ND 4/1FB	No
565135	8.5A19/LED/950/FR/P/ND 4/1FB	No

Operating and electrical

Order Code	Full Product Name	Input Frequency	Wattage Equivalent	Power (Nom)
549485	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	50 to 60 Hz	40 W	5 W
549493	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	50 to 60 Hz	60 W	8 W
545897	8.8A19/PER/940/P/E26/DIM 6/1FB T20	60 Hz	60 W	8.8 W
550400	5A19/PER/927/P/E26/DIM 6/1FB T20	60 Hz	40 W	5 W
550418	5A19/PER/930/P/E26/DIM 6/1FB T20	60 Hz	40 W	5 W
547042	5A19/PER/940/P/E26/DIM 6/1FB T20	60 Hz	40 W	5 W
550426	5A19/PER/950/P/E26/DIM 6/1FB T20	60 Hz	40 W	5 W
550434	8.8A19/PER/927/P/E26/DIM 6/1FB T20	60 Hz	60 W	8.8 W
550442	8.8A19/PER/930/P/E26/DIM 6/1FB T20	60 Hz	60 W	8.8 W
550459	8.8A19/PER/950/P/E26/DIM 6/1FB T20	60 Hz	60 W	8.8 W

Order Code	Full Product Name	Input Frequency	Wattage Equivalent	Power (Nom)
554485	16.6A21/LED/950/P/E26/ND 6/1FB T20	60 Hz	100 W	16.6 W
558239	29A21/PER/850/P/E26/DIM/HO 4/1FB	60 Hz	150 W	29 W
561019	16A19/PER/950/P/E26/DIM 6/1FB T20	60 Hz	100 W	16 W
561068	16A19/PER/927/P/E26/DIM 6/1FB T20	60 Hz	100 W	16 W
561076	16A19/PER/930/P/E26/DIM 6/1FB T20	60 Hz	100 W	16 W
561456	16A19/PER/940/P/E26/DIM 6/1FB T20	60 Hz	100 W	16 W
557660	8.8A19/PER/930/P/GU24/DIM 6/1FB T20	60 Hz	60 W	8.8 W
565119	8.5A19/LED/927/FR/P/ND 4/1FB	60 Hz	60 W	8.5 W
565127	8.5A19/LED/930/FR/P/ND 4/1FB	60 Hz	60 W	8.5 W
565135	8.5A19/LED/950/FR/P/ND 4/1FB	60 Hz	60 W	8.5 W

General information

Order Code	Full Product Name	Cap-Base	Nominal Lifetime (Nom)	Switching Cycle
549485	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	E26	15000 h	20000X
549493	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	E26	15000 h	20000X
545897	8.8A19/PER/940/P/E26/DIM 6/1FB T20	E26	15000 h	50000X
550400	5A19/PER/927/P/E26/DIM 6/1FB T20	E26	15000 h	50000X

Order Code	Full Product Name	Cap-Base	Nominal Lifetime (Nom)	Switching Cycle
550418	5A19/PER/930/P/E26/DIM 6/1FB T20	E26	15000 h	50000X
547042	5A19/PER/940/P/E26/DIM 6/1FB T20	E26	15000 h	50000X
550426	5A19/PER/950/P/E26/DIM 6/1FB T20	E26	15000 h	50000X
550434	8.8A19/PER/927/P/E26/DIM 6/1FB T20	E26	15000 h	50000X

A-Shape LED

Order Code	Full Product Name	Cap-Base	Nominal Lifetime (Nom)	Switching Cycle
550442	8.8A19/PER/930/P/E26/DIM 6/1FB T20	E26	15000 h	50000X
550459	8.8A19/PER/950/P/E26/DIM 6/1FB T20	E26	15000 h	50000X
554485	16.6A21/LED/950/P/E26/ND 6/1FB T20	E26	11000 h	50000X
558239	29A21/PER/850/P/E26/DIM/HO 4/1FB	E26	15000 h	50000X
561019	16A19/PER/950/P/E26/DIM 6/1FB T20	E26	15000 h	50000X
561068	16A19/PER/927/P/E26/DIM 6/1FB T20	E26	15000 h	50000X

Order Code	Full Product Name	Cap-Base	Nominal Lifetime (Nom)	Switching Cycle
561076	16A19/PER/930/P/E26/DIM 6/1FB T20	E26	15000 h	50000X
561456	16A19/PER/940/P/E26/DIM 6/1FB T20	E26	15000 h	50000X
557660	8.8A19/PER/930/P/GU24/DIM 6/1FB T20	GU24	15000 h	50000X
565119	8.5A19/LED/927/FR/P/ND 4/1FB	E26	11000 h	50000X
565127	8.5A19/LED/930/FR/P/ND 4/1FB	E26	11000 h	50000X
565135	8.5A19/LED/950/FR/P/ND 4/1FB	E26	11000 h	50000X

Light technical

Order Code	Full Product Name	Beam Angle (Nom)	Color Code	Correlated Color Temperature (Nom)	Color Rendering Index (Nom)	Luminous Flux (Nom)
549485	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	300 °	927-922	- K	90	450 lm
549493	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	300 °	927-922	- K	90	800 lm
545897	8.8A19/PER/940/P/E26/DIM 6/1FB T20	250 °	940	4000 K	90	800 lm
550400	5A19/PER/927/P/E26/DIM 6/1FB T20	250 °	927	2700 K	90	450 lm
550418	5A19/PER/930/P/E26/DIM 6/1FB T20	250 °	930	3000 K	90	450 lm
547042	5A19/PER/940/P/E26/DIM 6/1FB T20	250 °	940	4000 K	90	450 lm
550426	5A19/PER/950/P/E26/DIM 6/1FB T20	250 °	950	5000 K	90	450 lm
550434	8.8A19/PER/927/P/E26/DIM 6/1FB T20	250 °	927	2700 K	90	800 lm
550442	8.8A19/PER/930/P/E26/DIM 6/1FB T20	250 °	930	3000 K	90	800 lm
550459	8.8A19/PER/950/P/E26/DIM 6/1FB T20	250 °	950	5000 K	90	800 lm
554485	16.6A21/LED/950/P/E26/ND 6/1FB T20	210 °	950	5000 K	90	1500 lm
558239	29A21/PER/850/P/E26/DIM/HO 4/1FB	250 °	850	5000 K	80	2610 lm
561019	16A19/PER/950/P/E26/DIM 6/1FB T20	250 °	950	5000 K	90	1600 lm
561068	16A19/PER/927/P/E26/DIM 6/1FB T20	250 °	927	2700 K	90	1600 lm
561076	16A19/PER/930/P/E26/DIM 6/1FB T20	250 °	930	3000 K	90	1600 lm
561456	16A19/PER/940/P/E26/DIM 6/1FB T20	250 °	940	4000 K	90	1600 lm
557660	8.8A19/PER/930/P/GU24/DIM 6/1FB T20	250 °	930	3000 K	90	800 lm
565119	8.5A19/LED/927/FR/P/ND 4/1FB	150 °	927	2700 K	90	800 lm
565127	8.5A19/LED/930/FR/P/ND 4/1FB	150 °	930	3000 K	90	800 lm
565135	8.5A19/LED/950/FR/P/ND 4/1FB	150 °	950	5000 K	90	800 lm

Mechanical and housing

Order Code	Full Product Name	Bulb Finish	Bulb Shape	Order Code	Full Product Name	Bulb Finish	Bulb Shape
549485	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	Clear	A19 (A19)	550442	8.8A19/PER/930/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
549493	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	Clear	A19 (A19)	550459	8.8A19/PER/950/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
545897	8.8A19/PER/940/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)	554485	16.6A21/LED/950/P/E26/ND 6/1FB T20	Frosted	A21 (A21)
550400	5A19/PER/927/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)	558239	29A21/PER/850/P/E26/DIM/HO 4/1FB	Frosted	A21 (A21)
550418	5A19/PER/930/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)	561019	16A19/PER/950/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
547042	5A19/PER/940/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)	561068	16A19/PER/927/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
550426	5A19/PER/950/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)	561076	16A19/PER/930/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
550434	8.8A19/PER/927/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)	561456	16A19/PER/940/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)