



SKU: GBL-4DBT

UPC: 0783669960181

Features & Benefits:

Description:Permaground Copper Lay-in Groud Lug, Conductor Size 4-14, #10 Bolt Size, Slotted Head, Tin Plated

Specs

Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	Thru
Mounting Kit Hardware Part #	GBL-MHU
Number of Conductors	1
Number of Mounting Holes	1
Number of Ports / Wireways	1
Wire Orientation	NA

Dimensions

Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.825
Height BX (IN)	2.25
Length (IN)	1.15
Mounting Bolt/Stud Size (mm)	254
Mounting Hole Diameter (IN)	0.218
Mounting Hole Diameter (mm)	5.5372
Tang Length (IN)	0.47
Tang Length (mm)	11.938
Tang Thickness (IN)	0.185
Tang Thickness (mm)	4.699
Tang Width (IN)	0.375
Tang Width (mm)	9.525
Weight (LB)	0.06
Weight BX (LB)	3.9
Width (IN)	0.375
Width BX (IN)	5

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Nickel Strick, Zinc, Green Dye
Wire Binding Hardware Material	Stainless steel

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	1/4
Wire Binding Torque	10 - 14 AWG = 20

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-2
UPC Code	78366996018

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA