



SKU: ECTS-4-4

UPC: 0783669019445

Features & Benefits:

Description: Nimbus Insulated Aluminum Multi-Tap Connector, Conductor Range 4-14, 4 Ports, Single Sided Entry, Tin Plated, UL, CSA

Specs

Additional Class Attributes

| | |
|----------------------------|------------|
| Connection | Mechanical |
| Contains DE-OX® | Yes |
| Number of Conductors | 4 |
| Number of Poles | 1 |
| Number of Ports / Wireways | 4 |
| Number of Usable Ports | 4 |
| Number of Usable Taps | 4 |
| Replacement Part(s) | PLUG-4 |

Material and Finish

| | |
|--------------------------------|-------------------------------|
| Conductor Material | Aluminum |
| Connector Finish | Tin |
| Insulation Material | Plastisol |
| Wire Binding Hardware Finish | Zinc Clear Trivalent Chromate |
| Wire Binding Hardware Material | Steel |

Dimensions

| | |
|-----------------|--------------|
| Drive Size Main | 1/8 |
| Drive Type Main | Internal Hex |

Additional Technical Specifications

| | |
|----------------|-------|
| Conductor Type | Solid |
|----------------|-------|

Bolt and Screw Sizes

| | |
|--|------------|
| Number of Wire Binding Screws per Port | 1 |
| Wire Binding Screw Size | 1/4 |
| Wire Binding Torque | 2 AWG = 40 |

General

| | |
|--------------|---|
| Bag Quantity | 0 |
|--------------|---|

| | |
|------------------------------------|----------------|
| Carton Quantity Description | STD PACK QTY 6 |
| Dual Rated | Yes |
| NEMA Code | S-588-4 |
| UPC Code | 78366901944 |

Testing Standards

| | |
|---------------------------------|---|
| CSA File Number | LR-29601 |
| CSA Standard | C22.2 No. 65-03 |
| Prop65 Compliance | WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov |
| UL Control Number | 453G |
| UL / CULUS Specification | UL 486A/B Listed |
| UL File Number | E6207 |

Conductor Ranges

| | |
|---|-----------------|
| Conductor Range AL Stranded (Primary, run, main, line) | 4 Str - 14 Str |
| Conductor Range CU Solid (Primary, run, main, line) | 10 Sol - 14 Sol |
| Conductor Range CU Stranded (Primary, run, main, line) | 4 Str - 14 Str |
| Conductor Range AL Solid (Primary, run, main, line) | 10 Sol - 14 Sol |

Voltage

| | |
|-----------------------|-------|
| Voltage Rating | 600 V |
|-----------------------|-------|

Color

| | |
|-----------------------|-------|
| Cap Color Main | Black |
| Cap Color Tap | Black |
| Color | Clear |

Environment and Temperature

| | |
|---------------------------------|---------------------------------|
| Environmental Conditions | Cold temperature rated to -45°C |
| Flammability Rating | Insulation rated per UL 94 |
| Temperature Rating | 90°C |