



Representative Image

Catalog No. CL00A310TJ

Description: SERIES CL-CONTACTOR

UPC No

Home > Contactors > UL Listed IEC Contactors > Contactor

IEC Contactors. C-2000 Nonreversing and Reversing. AC Controlled, 3-Pole. HP Ratings AC-3 Duty. 5-75 Hp (460V) Nonreversing Standard Terminals. Maximum Current @ 460 V (A) AC-3: 10A. 1-Phase HP @60 Hz, 115V: 0.5. 1-Phase HP @60 Hz, 230V: 1.5. 3-Phase HP @60 Hz, 200V: 3. 3-Phase HP @60 Hz, 230V: 3. 3-Phase HP @60 Hz, 460V: 5. 3-Phase HP @60 Hz, 575V: 7.5. KW @ 50 Hz, 380/415V: 4. 10TJ SERIES CL-CONTACTOR

Descriptors

Category	Contactor
GO Schedule	C2

Specifications

Contacts	1NO
Coil Voltage	110 (50 Hz) / 120 (60 Hz)



Publications

Title	Publication No.	Publication Type
RL4 Relays	GEP1260-05-019	Drawings-Outline and Dimensional
RL4 Relays		

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.