



Representative Image

## Catalog No. CL04A310MJ

Description: "120VAC; 54A"

UPC No

[Home](#) > [Contactors](#) > [UL Listed IEC Contactors](#) > [Contactor](#)

IEC Contactors. C-2000 Nonreversing and Reversing. AC Controlled, 3-Pole. HP Ratings AC-3 Duty. 5-75 Hp (460V) Nonreversing Standard Terminals. Maximum Current @ 460 V (A) AC-3: 32A. 1-Phase HP @60 Hz, 115V: 2. 1-Phase HP @60 Hz, 230V: 5. 3-Phase HP @60 Hz, 200V: 10. 3-Phase HP @60 Hz, 230V: 10. 3-Phase HP @60 Hz, 460V: 20. 3-Phase HP @60 Hz, 575V: 25. KW @ 50 Hz, 380/415V: 16.

### Descriptors

Category	Contactor
GO Schedule	C2

### Specifications

Contacts	1NO
Coil Voltage	110 (50 Hz) / 120 (60 Hz)



## Publications

Title	Publication No.	Publication Type
<a href="#">C2000 CL04A310M</a> GEP1260-05-021C2000 CL04A310M	GEP1260-05-021	Drawings-Outline and Dimensional

**Additional Documentation:** Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.