


A-Shape LED


Application

- Ideal for decorative and ambient lighting in retail outlets, hotels, restaurants, multi-unit residences and government buildings.

Versions



Single Contact Medium Screw



Single Contact Medium Screw



E26 A21



Single Contact Medium Screw A19
(A19) Frosted

GU24 A19 (A19) Frosted







Single Contact Medium Screw A19
(A19) Frosted



A-Shape LED

Dimensional drawing



Product	D	C
5A19/PER/940/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
5A19/PER/927/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
8.8A19/PER/950/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
8.8A19/PER/927/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
8.8A19/PER/940/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
5A19/PER/930/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
5A19/PER/950/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
8.8A19/PER/930/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm



Product	D	C
8A19/PER/927-922/CL/G/E26/WGX 1FB T20	60 mm	108 mm
5A19/PER/927-922/CL/G/E26/WGX 1FB T20	60 mm	108 mm

Product	D	C
8.8A19/PER/930/P/GU24/DIM 6/1FB T20	60 mm	106 mm

Product	D	C
29A21/PER/850/P/E26/DIM/HO 4/1FB	77 mm	138 mm
16.6A21/LED/950/P/E26/ND 6/1FB T20	78 mm	140 mm

A-Shape LED

Dimensional drawing



Product	D	C
16A19/PER/940/P/E26/DIM 6/1FB T20	60 mm	112 mm
16A19/PER/950/P/E26/DIM 6/1FB T20	60 mm	112 mm
16A19/PER/927/P/E26/DIM 6/1FB T20	60 mm	112 mm
16A19/PER/930/P/E26/DIM 6/1FB T20	60 mm	112 mm

Product	D	C
8.5A19/LED/927/FR/P/ND 4/1FB	60 mm	104 mm
8.5A19/LED/930/FR/P/ND 4/1FB	60 mm	104 mm
8.5A19/LED/950/FR/P/ND 4/1FB	60 mm	104 mm

Operating and electrical

Voltage (Nom)	120 V
Starting Time (Nom)	0.5 s

Light technical

Llmf At End Of Nominal Lifetime (Nom)	70 %
---------------------------------------	------

Approval and application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
549485	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	- kWh
549493	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	- kWh
545897	8.8A19/PER/940/P/E26/DIM 6/1FB T20	- kWh
550400	5A19/PER/927/P/E26/DIM 6/1FB T20	- kWh
550418	5A19/PER/930/P/E26/DIM 6/1FB T20	- kWh
547042	5A19/PER/940/P/E26/DIM 6/1FB T20	- kWh
550426	5A19/PER/950/P/E26/DIM 6/1FB T20	- kWh
550434	8.8A19/PER/927/P/E26/DIM 6/1FB T20	- kWh
550442	8.8A19/PER/930/P/E26/DIM 6/1FB T20	- kWh
550459	8.8A19/PER/950/P/E26/DIM 6/1FB T20	- kWh

Order Code	Full Product Name	Energy Consumption kWh/1000 h
554485	16.6A21/LED/950/P/E26/ND 6/1FB T20	- kWh
558239	29A21/PER/850/P/E26/DIM/HO 4/1FB	-
561019	16A19/PER/950/P/E26/DIM 6/1FB T20	- kWh
561068	16A19/PER/927/P/E26/DIM 6/1FB T20	- kWh
561076	16A19/PER/930/P/E26/DIM 6/1FB T20	- kWh
561456	16A19/PER/940/P/E26/DIM 6/1FB T20	- kWh
557660	8.8A19/PER/930/P/GU24/DIM 6/1FB T20	-
565119	8.5A19/LED/927/FR/P/ND 4/1FB	-
565127	8.5A19/LED/930/FR/P/ND 4/1FB	-
565135	8.5A19/LED/950/FR/P/ND 4/1FB	-

Controls and dimming