



DVAKSX-LED14

Ceiling Mount LED Vapourproof



SPECIFICATIONS*

Watts	14W
Lumens	1585
Efficacy	111
Replaces Up To	100W Incandescent / 36W CFL Vapourproof fixture
Colour Temp	5000K*, 4000K, 3000K
Certification	ETL, DLC
Operating Temp	-40°C to 40°C
Voltage	120-277V
LED Life	50,000 hours
Housing Material	Aluminum
Lens Material	Polycarbonate
Power Factor	0.991
CRI	84
THD	10.8%

*Standard



DESCRIPTION

The DVAKSX-LED14 is a versatile fixture that can be used in industrial and architectural applications. The fixture is available in custom colours and has a variety of globe and guard accessories. Not for use in hazardous locations.

APPLICATIONS



Entrances



Stairwells



Tunnels



Service Areas



Restaurants



Elevator Shafts

FEATURES

- Sleek, modern look with the same ruggedness as the original DVAKS fixture.
- 10 minute retrofit. Retrofits to existing 4" round/octagon boxes.
- Polycarbonate lens can be easily replaced with glass globe and guard to provide a different look.
- Precision die cast aluminum housing with powder coat paint finish for industrial and architectural applications.
- Grey polyester powder coat paint finish for protection against oxidation.

ACCESSORIES

RAB Design carries a diverse line of durable and cost efficient glass globes. They come in various finishes, which include impregnated colours.

GLASS GLOBES OPTIONS (SOLD SEPARATELY)



GD100CGS CAST GUARD (SOLD SEPARATELY)



FEATURES

- Heavy duty raw/painted cast guard for use with RAB Design Vapourproof fixtures.
- Machined threads for smooth fit to RAB Design fixtures.
- Set screw to lock guard securely to fixture.

DVAKSX-LED14 shown with GD100CGS Cast Guard and GL100SB Sandblasted Globe.

ORDERING GUIDE

DVAKSX	LED14				
WATTS	VOLTAGE	COLOUR TEMP.	FINISH	FR	
	B - 120 - 277V	5K - 5000K*	DGY - DOVE GREY*	FR - FROSTED LENS*	
		4K - 4000K	CC - CUSTOM		
		3K - 3000K			

*Standard Configuration

FIELD INSTALLED ACCESSORIES:

CHECK THE ACCESSORIES YOU WISH TO ORDER:



Cast Guard - Raw
Finish GD100CGS



Cast Guard - Dove Grey
Finish GD100CGS-DGY



GL100
Clear Glass



GL100HR
Heat Resistant



GL100RIB
Ribbed Glass



GL100SB
Sandblasted



RGL100A
Amber



RGL100B
Blue



RGL100G
Green



RGL100R
Red