

## RIGID • IMC

Right Angle Clamp and Parallel Conduit Clamps for Rigid Conduit • IMC • EMT



### Applications

Designed to secure Rigid conduit, IMC, or EMT perpendicular to beam, channel and angle supports

### Features

- Two hex nuts\* - SRAC Series
- RoHS compliant

### Standard Materials

Steel U-Bolts and nuts\* - SRAC Series  
Malleable iron


### Standard Finish

Right Angle Clamp - Hot dip galvanized  
U-Bolt - Mechanically galvanized


### Applicable Third Party Standards

- UL Standard: 2239
- UL Listed File # E213669

\* SRAC Series only



SRACKON



SPARCKON

### Right Angle Conduit Clamp

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	DIM D	DIM E	MASTER PACK	WEIGHT PER C
SRAC50KON*	1/2"	1.000	1.250	2.500	1.813	2.063	50	34.9
SRAC75KON*	3/4"	1.125	1.375	2.813	1.813	2.250	50	38.6
SRAC100KON*	1"	1.375	1.625	3.063	1.813	2.563	50	43.8
SRAC125KON*	1-1/4"	1.750	2.000	3.188	1.813	2.875	25	48.5
SRAC150KON*	1-1/2"	2.000	2.375	3.500	1.813	3.250	25	54.8
SRAC200KON*	2"	2.500	2.500	4.500	2.625	4.063	25	92.6
SRAC250KON*	2-1/2"	3.000	3.250	4.875	2.625	4.500	10	106.5
SRAC300KON*	3"	3.625	3.875	5.375	2.625	5.125	10	126.4
SRAC350KON*	3-1/2"	4.063	4.563	5.875	2.625	5.625	10	136.0
SRAC400KON*	4"	4.688	5.063	6.688	2.625	6.125	10	163.4

### Parallel Conduit Clamps

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	MASTER PACK	WEIGHT PER C
SPARC50KON	1/2"	2.875	1.438	50	53.8
SPARC75KON	3/4"	3.063	1.688	50	59.7
SPARC100KON	1"	3.250	2.000	50	62.4
SPARC125KON	1-1/4"	3.625	2.125	25	80.6
SPARC150KON	1-1/2"	3.875	2.188	25	86.5
SPARC200KON	2"	4.625	2.875	25	99.6
SPARC250KON	2-1/2"	5.250	3.250	10	130.4
SPARC300KON	3"	5.875	3.875	10	161.2
SPARC350KON**	3-1/2"	6.313	4.313	10	190.4
SPARC400KON**	4"	6.813	4.813	10	210.0

\*\* Not UL Listed