

Rittal – The System.

Faster – better – everywhere.

► TopTherm chillers 1 - 6 kW – SK 3334.600

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm chillers 1 - 6 kW – SK 3334.600

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version:	Compact, modular layout of the refrigeration components Nano-coated condenser Pump to convey the medium
Benefits:	Precise temperature control, based on microprocessor technology Collective fault signal with floating contact One version for two frequencies = international compatibility
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 44 (electrics)
Supply includes:	Complete unit ready for connection Multilingual documentation including functional diagram and wiring plans
Note:	For 3334.660, two metal filters are required.
Note on Model No.::	Integral tank level display

Product features

Total cooling output:	With T _{sub} W _{subcl} = 10°C/T _{sub} U _{subcl} = 32°C and 50 Hz: 3.9 kW (13307 BTU) With T _{sub} W _{subcl} = 10°C/T _{sub} U _{subcl} = 32°C and 60 Hz: 4.7 kW (16037 BTU) With T _{sub} W _{subcl} = 18°C/T _{sub} U _{subcl} = 32°C and 50 Hz: 4.5 kW (15354 BTU) With T _{sub} W _{subcl} = 18°C/T _{sub} U _{subcl} = 32°C and 60 Hz: 5.4 kW (18425 BTU)
Air throughput (unimpeded air flow):	At 50 Hz: 1785 m ³ /h (1050.6 cfm) At 60 Hz: 1785 m ³ /h (1050.6 cfm)

Rated operating voltage:	400 V, 3~, 50 Hz 460 V, 3~, 60 Hz Note: Supports multiple voltages without rewiring.
Dimensions:	Height: 676 mm (27 ") Width: 602 mm (24 ") Depth: 645 mm (25 ")
Temperature control:	Microcontroller Control (factory setting +20°C)
Temperature range:	Operation (environment): +10°C...+43°C Liquid media: +10°C...+30°C
Temperature hysteresis:	± 2 K
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 1500 g (52.9 oz) Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO _{2e}): 2.15 t
Rated power P_{el}:	At 50 Hz: 2.88 kW At 60 Hz: 3.24 kW
Rated current (max.):	At 50 Hz: 5.6 A At 60 Hz: 6.15 A
Water circuit:	Open
Water connections:	G ½" internal thread
Number of cooling circuits:	1
Tank:	Content: 30 l Material: Plastic PP
Packaging unit:	1 pc(s).
Weight/packaging unit:	94 kg
EAN:	4028177351189
Customs tariff number:	84186900
ETIM 6.0:	EC002516
ETIM 5.0:	EC002516
eCl@ss 8.0/8.1:	27180713
eCl@ss 7.0/7.1:	27180713

eCl@ss 6.0/6.1:	27180713
eCl@ss 5.1/5.1.4:	27180713
Product description (long):	SK Chiller TopTherm, Stand alone, open, 4.5/5.4 kW, 400-460 V, 3~, 50/60 Hz, WHD: 602 x 676 x 645 mm
Approvals	
Approvals:	Approval overview
Certificates:	EAC
Declarations:	Declaration of conformity