

Rittal – The System.

Faster – better – everywhere.

► Profile rails, 482.6 mm (19") for TS – DK 7827.181

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Profile rails, 482.6 mm (19") for TS – DK 7827.181

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Benefits: Integral U markings in the front facilitate systematic assembly within the 19" level.
L rails accommodate the installation kits of server systems
Suitable for 19" partial expansion

Material: Carbon steel, 2 mm

Technical specifications: Integral 482.6 mm (19") punchings (EIA standard)
Side round and square punchings
Clear chromated for conductive connection of 19" fixtures

Supply includes: Assembly components

Product features

Suitable for: Enclosure type: TS
Height: 1800 mm (71 ")

Dimensions: Width: 19"

Height units: 38 U

Packaging unit: 2 pc(s).

Weight/packaging unit: 4.32 kg (9.5 lb.)

EAN: 4028177234925

Customs tariff 73269098

number:	
ETIM 6.0:	EC002620
ETIM 5.0:	EC002620
eCl@ss 8.0/8.1:	27189261
eCl@ss 7.0/7.1:	27189261
eCl@ss 6.0/6.1:	27189261
eCl@ss 5.1/5.1.4:	27182504
Product description (long):	DK-TS Mounting angles, 482.6 mm (19"), L-shaped mounting angle, For H: 1800 mm, 38 U