

# Rittal – The System.

Faster – better – everywhere.

## ➤ PK Polycarbonate Housings without knockouts – PK 9502.000

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# PK Polycarbonate Housings without knockouts – PK 9502.000

created: 29.05.2018 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

<b>Applications:</b>	Ambient temperature range: -35°C...+80°C The specified temperatures can be limited by the installed equipment
<b>Material:</b>	Housing: Fiber-glass reinforced polycarbonate Cover gray: Fiberglass-reinforced polycarbonate, all-round foamed PU seal Cover screws: Polyamide Insulating bungs: Polythene
<b>Color:</b>	RAL 7035
<b>Protection category IP to IEC 60 529:</b>	IP 66
<b>Protection category NEMA:</b>	NEMA 4X
<b>Supply includes:</b>	Housing with cover Cover screws Insulating bungs for wall mounting screws
<b>Base material:</b>	Polycarbonate

## Product features

<b>Dimensions:</b>	Height: 65 mm (2.6 ") Width: 94 mm (3.7 ") Depth: 57 mm (2.2 ")
<b>Cover:</b>	gray

<b>Ambient temperature range:</b>	-35°C...+80°C
<b>Packaging unit:</b>	8 pc(s).
<b>Weight/packaging unit:</b>	1.1 kg (2.4 lb.)
<b>EAN:</b>	4028177139015
<b>Customs tariff number:</b>	94037000
<b>ETIM 6.0:</b>	EC000261
<b>ETIM 5.0:</b>	EC002600
<b>eCl@ss 8.0/8.1:</b>	27180101
<b>eCl@ss 7.0/7.1:</b>	27180101
<b>eCl@ss 6.0/6.1:</b>	27180101
<b>eCl@ss 5.1/5.1.4:</b>	27180102
<b>Product description (long):</b>	PK Polycarbonate enclosure, WHD: 94x65x57 mm, fibreglass-reinforced polycarbonate, without knockouts, with grey cover
<b>Approvals</b>	
<b>Approvals:</b>	Bureau Veritas C-UL UL UL + C-UL
<b>Declarations:</b>	Declaration of conformity