Rittal – The System.

Faster – better – everywhere.

Steady light component for signal pillars, modular – SG 2369.000

Date : May 24, 2018



ENCLOSURES

POWER DISTRIBUTION >> CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Steady light component for signal pillars, modular – SG 2369.000

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version:	Steady light component
Description:	With 360° signal transmission thanks to optimized prism system. Number of potential stages = 5 components, with identical voltage.
Benefits:	Easy mounting and contact via bayonet fastener. Configuration of up to five components with the same voltage. Components are available in a range of colors and voltages.
Function principle:	A modular layout is possible with connection, optical and acoustic components, incandescent lamps and a label panel.
Material:	Housing of polyamide Cap: Transparent polycarbonate
Color:	Red
Protection category IP to IEC 60 529:	IP 54 if a cover or acoustic component is fitted at the top
Note on Model No.::	Incandescent lamps not included with the supply.
Product features	
Dimensions:	Height: 56 mm Diameter: 70 mm
Rated operating	12 V - 240 V (AC/DC)

1

voltage:	
Diameter:	70 mm
Rated insulation voltage:	250 V AC
Rated impulse withstand voltage, phase to phase:	2500 V AC
Packaging unit:	1 pc(s).
Weight/packaging unit:	0.09 kg (0.2 lb.)
EAN:	4028177219922
Customs tariff number:	85311095
ETIM 6.0:	EC000232
ETIM 5.0:	EC000232
e Cl@ss 8.0/8.1:	27371220
eCl@ss 7.0/7.1:	27371220
eCl@ss 6.0/6.1:	27371220
eCl@ss 5.1/5.1.4:	27371220
Product description (long):	SG Steady light component, for signal pillar, modular, 12-240 V, AC/DC, red
Approvals	
Approvals:	C-UL UL + C-UL UR
Certificates:	EAC
Declarations:	Declaration of conformity