Rittal - The System.

Faster – better – everywhere.

Conductor TerminalsSV 3453.500


Date: May 24, 2018



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Conductor Terminals – SV 3453.500

created: 24.05.2018 build on www.rittal.com/us-en



Product description	
Description:	For connecting round conductors and laminated copper bars.
Material:	Carbon steel
Surface finish:	Zinc-plated, passivated
Note:	Wire end ferrules should be used with fine stranded wire conductors.
Product features	
Suitable for busbars:	Cross-section (thickness): 5 mm
Clamping area for laminated copper bars:	Height: 15 mm Width: 16.5 mm (0.65 ")
Connection for round conductor cross-sections:	35 mm² - 70 mm²
Packaging unit:	15 pc(s).
Weight/packaging unit:	1.68 kg (3.7 lb.)
EAN:	4028177042704
Customs tariff number:	85369010
ETIM 6.0:	EC000001
A© Rittal 2018	

ETIM 5.0:	EC000001
eCl@ss 8.0/8.1:	27141146
eCl@ss 7.0/7.1:	27141146
eCl@ss 6.0/6.1:	27141146
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV Conductor connection clamp, 35-70 mm², clamping area WH: 16,5x15 mm, for bar thickness 5 mm
Approvals	
Approvals:	C-UR UR
Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2018