

Rittal – The System.

Faster – better – everywhere.

Conductor Terminals **– SV 3458.500**

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE


SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Conductor Terminals – SV 3458.500

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Description: For connecting round conductors and laminated copper bars.

Material: Carbon steel

Surface finish: Zinc-plated, passivated

Note: Wire end ferrules should be used with fine stranded wire conductors.

Product features

Suitable for busbars: Cross-section (thickness): 10 mm

Clamping area for laminated copper bars:
Height: 15 mm
Width: 16.5 mm (0.65 ")

Connection for round conductor cross-sections: 35 mm² - 70 mm²

Packaging unit: 15 pc(s).

Weight/packaging unit: 1.66 kg (3.7 lb.)

EAN: 4028177042766

Customs tariff number: 85369010

ETIM 6.0: EC000001

ETIM 5.0:	EC000001
eCl@ss 8.0/8.1:	27141146
eCl@ss 7.0/7.1:	27141146
eCl@ss 6.0/6.1:	27141146
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV Conductor connection clamp, 35-70 mm ² , clamping area WH: 16,5x15 mm, for bar thickness 10 mm
Approvals	
Approvals:	C-UR UR
Certificates:	EAC
Declarations:	Declaration of conformity