Rittal - The System.

Faster – better – everywhere.



Date: May 25, 2018



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

E-Box EB - EB 1549.500

created: 25.05.2018 build on www.rittal.com/us-en



Material:	Housing and door: Carbon steel, all-round foamed-in PU seal
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category P to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
K code:	IK08
Supply includes:	Housing with hinged door 180° hinge Cam lock with 3 mm double-bit insert Mounting plate
Base material:	Carbon steel

Dimensions: Height: 200 mm (7.9 ")

Width: 200 mm (7.9 ") Depth: 120 mm (4.7 ")

Material thickness:: Housing: 1.25 mm (0.05 ")

Door: 1.25 mm (0.05 ") Mounting plate: 2 mm (0.08 ")

© Rittal 2018

Mounting plate:	Height: 185 mm (7.3 ") Width: 175 mm (6.9 ")
Lock version:	Cam
No. of locks:	1
Lock Insert:	3 mm double-bit
Packaging unit:	1 pc(s).
Weight/packaging unit:	2.8 kg
EAN:	4028177251700
Customs tariff number:	94032080
ETIM 6.0:	EC002713
ETIM 5.0:	EC000261
e Cl@ss 8.0/8.1:	27180101
e Cl@ss 7.0/7.1:	27180101
e Cl@ss 6.0/6.1:	27180101
e CI@ss 5.1/5.1.4:	27180102
Product description (long):	EB E-Box, WHD: 200x200x120, Sheet steel, with mounting plate, with door
Approvals	
Approvals:	Bureau Veritas C-UL CSA Lloyds Register of Shipping RRR Russian Maritime Register of Shipping TÜV UL UL + C-UL
Certificates:	EAC IK-Code
	Declaration of conformity

© Rittal 2018