

Rittal – The System.

Faster – better – everywhere.

► **TopTherm wall-mounted cooling units, horizontal format Total cooling output 0.30 kW – SK 3302.310**

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm wall-mounted cooling units, horizontal format Total cooling output 0.30 kW – SK 3302.310

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Carbon steel
Color:	RAL 7035
Protection category IP to IEC 60 529:	External circuit, IP 34 Internal circuit, IP 54
Supply includes:	Nano-coated condenser Wired ready for connection (plug-in terminal strip) Drilling template Fasteners

Product features

Total cooling output to DIN EN 14511:	L 35 L 35 at 60 Hz: 0.38 kW (1296 BTU) L 35 L 50 at 60 Hz: 0.23 kW (784 BTU)
Air throughput (unimpeded air flow):	External circuit: 300 m ³ /h (176.6 cfm) Internal circuit: 300 m ³ /h (176.6 cfm)
Rated operating voltage:	115 V, 1~, 60 Hz
Dimensions:	Height: 340 mm (13 ") Width: 525 mm (21 ") Depth: 153 mm (6 ")
Temperature control:	Basic Controller (factory setting +35°C)

Temperature range:	Operation (environment): +10°C...+55°C Setting range: +30°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 95 g (3.4 oz) Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO _{2e}): 0.13 t
Rated power P_{el}:	L 35 L 35 at 60 Hz: 0.32 kW L 35 L 50 at 60 Hz: 0.37 kW
Rated current (max.):	At 60 Hz: 4 A
Start-up current (max.):	At 60 Hz: 12 A
Miniature circuit-breaker/fuse:	10 A
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	1.18
Packaging unit:	1 pc(s).
Weight/packaging unit:	13 kg (28.7 lb.)
EAN:	4028177429802
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704
eCl@ss 6.0/6.1:	27180704
eCl@ss 5.1/5.1.4:	27180704
Product description (long):	SK cooling unit TopTherm, wall-mounted, horizontal format, 0.38 kW, 115 V, 1~, 60 Hz, Sheet steel, WHD: 525 x 340 x 153 mm

Approvals

Approvals:	TÜV-Geprüfte Leistung TÜV-Geprüfte Sicherheit UL + C-UL - FTTA
-------------------	--

UR + C-UR

Certificates:

EAC

Declarations:

Declaration of conformity
Declaration of conformity - F-gas regulation
