Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.570

Date : May 29, 2018



ENCLOSURES

POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wallmounted enclosure – WM 8017.570 - WM483610NC

created: 29.05.2018 build on www.rittal.com/us-en



Product description	
Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes 3-point latching L-Handle
Product features	
Dimensions:	Height: 1200 mm (47 ″) Width: 900 mm (35 ″) Depth: 250 mm (9.8 ″)
Material thickness::	Housing: 2 mm (0.08 ″) Door: 2 mm (0.08 ″) Mounting plate: 2.5 mm (0.1 ″)
Mounting plate:	Height: 1155 mm (45 ″) Width: 840 mm (33 ″)

3-point locking system:	yes
Packaging unit:	1 pc(s).
Weight/packaging unit:	81 kg (178.6 lb.)
EAN:	83149
Approvals	
Approvals:	UL