Rittal - The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.586

Date: May 24, 2018



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Wallmounted enclosure - WM 8017.586 - WM423612NC

created: 24.05.2018 build on www.rittal.com/us-en



D 1 1		
Product	des	crintion
1 IOGGC	aco	01160011

Material: Door: Carbon steel, all-round foamed-in PU seal

Housing: Carbon steel

Surface finish: Housing and door: Dipcoat primed, powder-coated on the outside, textured paint

Mounting plate: Zinc-plated

Color: RAL 7035

Protection category IP to IEC 60 529:

IP 66

Protection category

NEMA:

NEMA 4

Supply includes: Housing with door(s)

Left hand hinge Mounting plate

Rear wall mounting holes 3-point latching L-Handle

Product features

Dimensions: Height: 1050 mm (41 ")

Width: 900 mm (35 ") Depth: 300 mm (12 ")

Material thickness:: Housing: 2 mm (0.08 ")

Door: 2 mm (0.08 ")

Mounting plate: 2.5 mm (0.1 ")

Mounting plate: Height: 1020 mm (40 ")

Width: 840 mm (33 ")

© Rittal 2018

3-point locking system:	yes
Packaging unit:	1 pc(s).
Weight/packaging unit:	77 kg (169.8 lb.)
EAN:	83163
Approvals	
Approvals:	UL

© Rittal 2018 2