Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.533 Date : May 24, 2018

RITTAL



POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wallmounted enclosure – WM 8017.533 - WM202006NC

created: 24.05.2018 build on www.rittal.com/us-en



Product description	
Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert
Product features	
Dimensions:	Height: 500 mm (20 ″) Width: 500 mm (20 ″) Depth: 150 mm (5.9 ″)
Material thickness::	Housing: 1.5 mm (0.06 ″) Door: 1.5 mm (0.06 ″) Mounting plate: 2.5 mm (0.1 ″)
Mounting plate:	Height: 475 mm (19 ″) Width: 449 mm (18 ″)

1

Packaging unit:	1 pc(s).
Weight/packaging unit:	17 kg (37.5 lb.)
EAN:	83120
Approvals	
Approvals:	UL