

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 8017.541

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure – WM 8017.541 - WM162008NC

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert

Product features

Dimensions:	Height: 400 mm (16 ") Width: 500 mm (20 ") Depth: 210 mm (8.3 ")
Material thickness::	Housing: 1.5 mm (0.06 ") Door: 1.5 mm (0.06 ") Mounting plate: 1.5 mm (0.06 ")
Mounting plate:	Height: 375 mm (15 ") Width: 449 mm (18 ")

Packaging unit:	1 pc(s).
Weight/packaging unit:	10 kg (22 lb.)
EAN:	83125
Approvals	
Approvals:	UL