## Rittal - The System.

Faster – better – everywhere.

## Wallmounted enclosure – WM 8017.590

Date: May 24, 2018



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

## Wallmounted enclosure - WM 8017.590 - WM484812NC

created: 24.05.2018 build on www.rittal.com/us-en



Pro	duct	des	crip	tion
	auci	ucs	OLIP	LIVII

Material: Door: Carbon steel, all-round foamed-in PU seal

Housing: Carbon steel

**Surface finish:** Dipcoat-primed and powder-coated, textured paint

Mounting plate: Zinc-plated

Color: RAL 7035

Protection category IP to IEC 60 529:

IP 55

**Protection category** 

NEMA:

NEMA 12 NEMA 12

**Supply includes:** Housing with door(s)

Mounting plate

Rear wall mounting holes

## **Product features**

**Dimensions:** Height: 1200 mm (47 ")

Width: 1200 mm (47 ") Depth: 300 mm (12 ")

Material thickness:: Housing: 2 mm (0.08 ")

Door: 2 mm (0.08 ")

Mounting plate: 2.5 mm (0.1 ")

Mounting plate: Height: 1150 mm (45 ")

Width: 1150 mm (45 ")

© Rittal 2018

1

Number of doors:	2
3-point locking system:	yes
Packaging unit:	1 pc(s).
Weight/packaging unit:	93 kg (205 lb.)
EAN:	83167
Approvals	
Approvals:	UL

© Rittal 2018 2