Rittal - The System.

Faster – better – everywhere.

Fuse Holders 61 A to 400 A – SV 9345.200

Date: May 24, 2018



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Fuse Holders 61 A to 400 A - SV 9345.200

created: 24.05.2018 build on www.rittal.com/us-en



Product description	1
Version:	For busbar systems
Material:	Polyamide (PA 6) Fire protection corresponding to UL 94-V0 Contact tracks: Electrolytic copper, silver-plated
Color:	Chassis: RAL 7035 Cover: RAL 7035/7001
Note:	UL (listed accessory) is met through use of the fuse holder on RiLine busbar systems
Product features	
Suitable for busbars:	with cross-section height: 5 mm (0.2 ") with cross-section height: 10 mm (0.39 ")
Number of poles:	3-pole
For bar systems with center-to-center spacing:	60 mm
Dimensions:	Height: 288 mm (11 ") Width: 210 mm (8.3 ")
Type of connection (electrical):	Box terminal
Rated operating voltage:	600 V, 3~

© Rittal 2018

Connection for round conductor cross-sections:	AWG 4/0 – MCM 600
Rated operating current min.:	101 A
Rated operating current max.:	200 A
Cable outlet:	Top/bottom
Suitable for fuses:	Fuse type (class): J Fuse standard: UL 4248-8 Ø x length: 41 mm x 146 mm
Packaging unit:	1 pc(s).
Weight/packaging unit:	3.94 kg (8.7 lb.)
EAN:	4028177615663
Customs tariff number:	85365080
ETIM 6.0:	EC001900
ETIM 5.0:	EC001900
e Cl@ss 8.0/8.1:	27400613
e CI@ss 7.0/7.1:	27400613
e CI@ss 6.0/6.1:	27400613
e CI@ss 5.1/5.1.4:	27370302
Product description (long):	SV Fuse holder, Class J, 101-200 A, 600 V, 3-pole, (60 mm)
Approvals	
Approvals:	C-UR UL + C-UL UR
Certificates:	EAC

© Rittal 2018 2