

# Rittal – The System.

Faster – better – everywhere.

## ► Support rail 75 x 20 mm for TS, SE, CM – TS 4396.500

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Support rail 75 x 20 mm for TS, SE, CM – TS 4396.500

created: 24.05.2018 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

**Version:** unslotted

**Description:** For heavy equipment such as base isolators or transformers.

**Material:** Carbon steel

**Surface finish:** Zinc-plated

**Supply includes:** Assembly components

## Product features

**Suitable for:** Enclosure type: TS 8  
Enclosure type: SE  
Enclosure type: CM  
Width: 600 mm (24 ")  
Depth: 600 mm (24 ")

**Installation options:** On the vertical TS, SE enclosure section via snap-on nuts 8800.806 or via adapter rail for PS compatibility, offset in the height, via TS punched rail 25 x 38 mm  
On the horizontal TS enclosure section: in the width, in the depth  
in the case of SE, may additionally be fitted to the horizontal section in the width at the bottom and top, or in the depth at the top using snap-on nut 8800.808  
On base configuration rail for CM

**Packaging unit:** 4 pc(s).

**Weight/packaging unit:** 7.14 kg (15.7 lb.)

**EAN:** 4028177522787

---

**Customs tariff number:** 73269098

---

**ETIM 6.0:** EC001285

---

**ETIM 5.0:** EC001285

---

**eCl@ss 8.0/8.1:** 27189261

---

**eCl@ss 7.0/7.1:** 23159101

---

**eCl@ss 6.0/6.1:** 23159101

---

**eCl@ss 5.1/5.1.4:** 27189250

---

**Product description (long):** TS Support rail, for TS, SE, CM, for W/D: 600 mm, unslotted

---