Rittal - The System.

Faster – better – everywhere.

Wallmountedenclosure Stainlesssteel – WM 8017.603

Date: May 24, 2018



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Wallmounted enclosure Stainless steel - WM 8017.603 -WM242008N4

created: 24.05.2018 build on www.rittal.com/us-en



Prod	uct	des	crin	tion
riuu	uci	ues	CHID	เมษา

Material: Door: Stainless steel, all-round foamed-in PU seal

Housing and door: Stainless steel 1.4301 (AISI 304)

Mounting plate: Carbon steel, zinc-plated

Surface finish: Brushed

Protection category IP 66

IP to IEC 60 529:

Protection category NEMA:

NEMA 4X

Supply includes: Housing with door(s) Left hand hinge

Mounting plate

Wall mounting blind-nuts

Product features

Dimensions: Height: 600 mm (24 ")

Width: 500 mm (20 ") Depth: 210 mm (8.3 ")

Material thickness:: Housing: 1.5 mm (0.06 ")

Door: 1.5 mm (0.06 ")

Mounting plate: 2.5 mm (0.1 ")

Height: 570 mm (22 ") Mounting plate:

Width: 449 mm (18")

© Rittal 2018

1

Lock version:	Quarter turn
Packaging unit:	1 pc(s).
Weight/packaging unit:	21 kg (46.3 lb.)
EAN:	83180
Approvals	
Approvals:	UL + C-UL

© Rittal 2018