

# Straight Blade Devices

## 15A 125V, 2- Pole 3-Wire Grounding

### Tamper Resistant Duplex Receptacle

# HUBBELL

#### Features

- Smooth indented face appearance
- Multiple-drive Slot/Phillips/Robertson head screws
- Tough thermoplastic ultrasonically welded cover and base

#### Ordering Information

Description	Device Color	UPC	Catalog Number
Tamper Resistant- Self Grounding Duplex Receptacle	White	883778301544	RR15SWTR

#### Listings

UL Listed to UL 498  
CSA Certified 22.2, No. 42



#### Specifications

Face	PVC
Base	PVC
Power Contacts	.030 in. (.8mm) Brass
Ground Contacts	.014 in. (.35mm) Brass
Terminal Screws	Plated Steel
Automatic Self-grounding Staple	Stainless steel
Mounting Screws	Zinc Plated Steel

#### Performance

Electrical	
Current Interrupting	Certified for current interrupting at full rated current
Dielectric Voltage	Withstands 1,500V minimum

#### Mechanical

Terminal	Terminal screws accepts up to #12 AWG, Push wire designed for #14 AWG solid copper wire only
----------	----------------------------------------------------------------------------------------------

#### Environmental

Flammability	UL 94 V-2
Operating Temperatures	-20°C to 60°C

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

