DR60RF-WH/BK/SN

Job Information	Dimming 10%-100% dimming capability Compatible with industry TRIAC/ELV dimmers (contact factory for listing of compatible dimmers) 		
Project Type Type			
Location Quantity Date	Environment		
Contact/ Name	 Suitable for damp locations Suitable for insulated ceiling application Can be installed indoor and for outdoor applications 		
Notes	Mounting Included two spring loaded cilps to attach to any ceilling material The slim profile allows to be mounted under joists or dock work 		
	Description • DR60RF, a 15 watt 6-inch 5CCT slim profile round flat LED panel is a high-performance, easy to install downlight. It offers excellent light output, energy efficiency and steamlined design. Suitable for damp location and use in soffits.		
	Beam Spread • 110 degree beam spread		
Body • Durable airtight aluminum • White polycarbonate diffuser lens for low glare	LED Driver • Extruded aluminum junction box with integrated 210mA dimmable driver included • Class II electronic LED driver with 100-125V AC input; • includeds an 12" cable from driver to fixture		
LED Characteristics • 15-Watt LED Module • Minimal heat emission	Quick Connect Push-in Terminals Three "Quick Connect" Push-in terminals for fast and easy wiring 		
 Up to 1,280 Lumens Superior LED Performance and lifespan Excellent Color rendering with Spotlight 	Operating Temperature • -20℃ - 40℃ (-4°F - 104°F)		

SPECIFICATION			
Application	Ceiling Recess Mount	Energy Star	YES
Approved Location	Damp	Input	100-125V AC, 60Hz, 0.09A
Beam Angle	110	LM 79	YES
CTT (5CCT in one)	2700K/3000K/3500K/4000K/5000K	LM 80	YES
Certification	cETLus	Lumens	1,280
Class II	YES	Lumens per Watt	66.67
Color	White/Black/Brushed Nickel	Power Factor	>0.95
CRI	80+	Projected Life	5 Years
Dimming	YES	Wattage	15 Watt
Dimming Tech	TRIAC/ELV	Cut-Size	6 1/8"



Zotia International Trade Ltd.T: 905-669-1966201 Rowntree Dairy RoadF: 905-851-5262 Woodbridge, ON, L4L 8B8

E: sales@zotia.ca W: www.dawnray.ca



