
# Eaton C25FGF360A

## Catalog number: C25FGF360A

Eaton definite purpose contactor, Quick, 60A, 110-120 Vac, 50/60 Hz, NEMA Type 1 Enclosed, 15-50A, two- and three-pole, 60A, Contactor, Three-pole, Box lugs (posidrive setscrew) and quick connect terminals (side-by-side), Non-reversing

#### General specifications



. .

UPC

782113621609

**Product Height** 

9.51 in

**Product Weight** 

6.3 lb

Compliances

**RoHS Compliant** 

Catalog Number

C25FGF360A

Product Length/Depth

4.81 in

Product Width

5.62 in

Warranty

1 year

Certifications

CSA Certified UL Recognized



F:T·N

### defaultTaxonomyAttributeLabel

Frame size

15-50 A, two-pole and three-pole

Type

Non-reversing

Inductive full load

60 A

Model

Contactor

Connection

Quick

**Enclosure** 

NEMA type 1 enclosed

Terminals

Box lugs (posidrive setscrew) and quick connect terminals (sideby-side)

Amperage Rating

60A

Coil

110-120 Vac, 50/60 Hz

#### Resources

#### Catalogs

Eaton's Volume 5—Motor Control and Protection

Specifications and datasheets

Eaton Specification Sheet - C25FGF360A



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2022 Eaton All Rights Reserved Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia