

Eaton C25KNE3200A

Catalog number: C25KNE3200A

Eaton definite purpose contactor,200A, 110-120 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 200A, Contactor, Three-pole, 200 and 300A, three-pole, 200A, Box lugs (posidrive setscrew), Non-reversing



General specifications

Product Name	Catalog Number
Eaton definite purpose contactor	C25KNE3200A
UPC	Product Length/Depth
782114183939	7.25 in
Product Height	Product Width
9.11 in	7.05 in
Product Weight	Warranty
21.9 lb	1 year
Compliances	Certifications
RoHS Compliant	CSA Certified UL Recognized
Catalog Notes	
Resistive Load rating per pole	

defaultTaxonomyAttributeLabel

Contact configuration

1 NO, 1 NC

Frame size

15-50 A, two-pole and three-pole

Type

Non-reversing

Inductive full load

200 A

Model

Contactor

Connection

Quick

Size

200 and 300A, three-pole

Enclosure

Open with metal mounting plate

Terminals

Box lugs (posidrive setscrew)

Amperage Rating

200A

Resistive load

200 A

Coil

110-120 Vac, 50/60 Hz

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[C25KNE3 2D PDF](#)

[C25KNE3 AutoCAD 2D Footprint](#)

[C25KNE3 3D Model Xchange](#)

[C25KNE3 3D Inventor](#)

[C25KNE3 AutoCAD 2D Footprint \(mm\)](#)

[C25KNE3 2D Drawing Xchange](#)

Specifications and datasheets

[Eaton Specification Sheet - C25KNE3 200A](#)